

ClimaTemp Revolt 5000 LGR Dehumidifier

The Workhorse of LGR Dehumidifiers

The Revolt LGR 5000 is a proven workhorse with a market leading 130Pints/day of moisture removal and 230 Pints/day at saturation. This LGR dehumidifier is perfect for any moisture removal project including remediation jobs, flooding applications, or any high humidity environments. The Revolt combines proven design with professional performance and portability. For monitoring, the Revolt 5000 has a full digital display which features inlet/outlet temperature and relative humidity. The rotomolded polyethylene housing is scratch resistant and offers superior durability. Each unit is stackable and incorporates an adjustable handle. For ease of mobility, semi-pneumatic wheels compliment the Revolt to navigate any jobsite.

REVOLT 5000 LGR SPECIFICATIONS



Voltage & Hertz
Power Consumption & Current

REFRIGERANT CHARGE
DEHUMIDIFY CAPACITY

MAXIMUM DESIGN PRESSURE

FAN MOTOR POWER

AC115V / 60Hz
945W/8.3A @80°F, 60% RH
1140W/10.6A @86°F, 80% RH
R410A/26.8oz (760G)
130PINTS/DAY AHAM @80°F, 60% RH
200PINTS/DAY @86°F, 80% RH
230PINTS/DAY @SATURATION
HIGH SIDE: 522PSIG (3.6MPA)
LOW SIDE: 240PSIG (1.65MPA)
0.187HP



1-844-349-5665 www.Clima-Temp.com