

INSTALLATION INSTRUCTIONS ADDENDUM

Addendum for High kW Electric Heat Electrical Data on (-)HSA/(-)HSL, (-)HLA/(-)HLL

NORMAL COOLING CAPACITY TONS CABINET SIZE	Model No.	HEATER kW 208/240V	PH/HZ	NO. ELEMENTS - kW PER	TYPE SUPPLY CIRCUIT SINGLE CIRCUIT MULTIPLE CIRCUIT	CIRCUIT AMPS.	MOTOR AMPACITY	MINIMUM CIRCUIT AMPACITY	MAXIMUM CIRCUIT PROTECTION
(-)HSA/(-)HSL 1-1/2 & 2 17	RXBH-17A13J	9.4/12.5	1/60	3-4.17	SINGLE	45.1/52.1	1.7	59/68	60/ 70
	RXBH-17A13J	3.1/4.2	1/60	1-4.17	MULTIPLE CKT 1	15.0/17.4	1.7	21/24	25/ 25
		6.3/8.3	1/60	2-4.17	MULTIPLE CKT 2	30.1/34.7	0	40/45	38/ 44
RXBH-17A13C	9.4/12.5	3/60	3 - 4.17	SINGLE	26.1/30.1	1.7	35/40	35/ 40	
(-)HSA/(-)HSL 2-1/2 & 3 17	RXBH-17A13J	9.4/12.5	1/60	3-4.17	SINGLE	45.1/52.1	2.5	60/69	60/ 70
	RXBH-17A13J	3.1/4.2	1/60	1-4.17	MULTIPLE CKT 1	15.0/17.4	2.5	22/25	25/ 25
		6.3/8.3	1/60	2-4.17	MULTIPLE CKT 2	30.1/34.7	0	38/44	40/ 45
	RXBH-17A18J	12.8/17.0	1/60	3-5.68	SINGLE	61.6/70.8	2.5	81/92	90/ 100
	RXBH-17A18J	4.3/5.7	1/60	1-5.68	MULTIPLE CKT 1	20.5/23.6	2.5	29/33	30/ 35
		8.5/11.3	1/60	2 - 5.68	MULTIPLE CKT 2	41.1/47.2	0	52/59	60/ 60
	RXBH-17A13C	9.4/12.5	3/60	3 - 4.17	SINGLE	26.1/30.1	2.5	36/41	40/ 45
	RXBH-17A18C	12.8/17.0	3/60	3-5.68	SINGLE	35.5/41.0	2.5	48/55	50/ 60
RXBH-17A18D	17	3/60	3 - 5.68	SINGLE	20.4	1.4	28	30	
(-)HSA/(-)HSL 3 21	RXBH-24A18J	12.8/17.0	1/60	4-4.26	SINGLE	61.6/70.8	2.5	81/92	90/ 100
	RXBH-24A18J	6.4/8.5	1/60	2 - 4.26	MULTIPLE CKT 1	30.8/35.4	2.5	42/48	45/ 50
		6.4/8.5	1/60	2 - 4.26	MULTIPLE CKT 2	30.8/35.4	0	39/45	40/ 45
	RXBH-24A18C	12.8/17.0	3/60	3-5.68	SINGLE	35.5/41.0	2.5	48/55	50/ 60
	RXBH-24A18D	17	3/60	3 - 5.68	SINGLE	20.4	1.4	28	30
(-)HSA/(-)HSL 3-1/2 & 4 21 and 4 24	RXBH-24A25J	18.0/24.0	1/60	6-4.0	SINGLE	86.4/99.9	4.0	113/130	125/ 150
	RXBH-24A25J (4-ton only)	6.0/8.0	1/60	2 - 4.0	MULTIPLE CKT 1	28.8/33.3	4.0	42/47	45/ 50
		6.0/8.0	1/60	2 - 4.0	MULTIPLE CKT 2	28.8/33.3	0.0	36/42	40/ 45
		6.0/8.0	1/60	2 - 4.0	MULTIPLE CKT 3	28.8/33.3	0.0	36/42	40/ 45
	RXBH-24A25C	18.0/24.0	3/60	6-4.0	SINGLE	50.0/57.8	4.0	68/78	70/ 80
	RXBH-24A25C (4-ton only)	9.0/12.0	3/60	3 - 4.0	MULTIPLE CKT 1	25.0/28.9	4.0	37/42	40/ 45
		9.0/12.0	3/60	3 - 4.0	MULTIPLE CKT 2	25.0/28.9	0.0	32/37	35/ 40
RXBH-24A25D (4-ton only)	24.0	3/60	6 - 4.0	SINGLE	28.8	2.2	39	40	
(-)HSA/(-)HSL 5 24	RXBH-24A30C	21.6/28.8	3/60	6-4.8	SINGLE	60.0/69.4	4.4	81/93	90/ 100
	RXBH-24A30C	10.8/14.4	3/60	3 - 4.8	MULTIPLE CKT 1	30.0/34.7	4.4	43/49	45/ 50
		10.8/14.4	3/60	3 - 4.8	MULTIPLE CKT 2	30.0/34.7	0	38/44	40/ 45
	RXBH-24A30D	28.8	3/60	6 - 4.8	SINGLE	34.6	2.2	46	50
(-)HLA/(-)HLL 1-1/2 & 2 17	RXBH-17A13J	9.4/12.5	1/60	3-4.17	SINGLE	45.1/52.1	1.6	59/68	60/ 70
	RXBH-17A13J	3.1/4.2	1/60	1-4.17	MULTIPLE CKT 1	15.0/17.4	1.6	21/24	25/ 25
		6.3/8.3	1/60	2-4.17	MULTIPLE CKT 2	30.1/34.7	0	38/44	40/ 45
	RXBH-17A13C	9.4/12.5	3/60	3 - 4.17	SINGLE	26.1/30.1	1.6	35/40	35/ 40
(-)HLA/(-)HLL 2-1/2 & 3 17	RXBH-17A13J	9.4/12.5	1/60	3-4.17	SINGLE	45.1/52.1	2.7	60/69	60/ 70
	RXBH-17A13J	3.1/4.2	1/60	1-4.17	MULTIPLE CKT 1	15.0/17.4	2.7	23/26	25/ 30
		6.3/8.3	1/60	2-4.17	MULTIPLE CKT 2	30.1/34.7	0	38/44	40/ 45
	RXBH-17A18J	12.8/17.0	1/60	3-5.68	SINGLE	61.6/70.8	2.7	81/92	90/ 100
	RXBH-17A18J	4.3/5.7	1/60	1-5.68	MULTIPLE CKT 1	20.5/23.6	2.7	29/33	30/ 35
		8.5/11.3	1/60	2 - 5.68	MULTIPLE CKT 2	41.1/47.2	0	52/59	60/ 60
	RXBH-17A13C	9.4/12.5	3/60	3 - 4.17	SINGLE	26.1/30.1	2.7	36/41	40/ 45
	RXBH-17A18C	12.8/17.0	3/60	3-5.68	SINGLE	35.5/41.0	2.7	48/55	50/ 60
(-)HLA/(-)HLL 3-1/2 & 4 21	RXBH-24A25J	18.0/24.0	1/60	6-4.0	SINGLE	86.4/99.9	3.8	113/130	125/ 150
	RXBH-24A25J (4-ton only)	6.0/8.0	1/60	2 - 4.0	MULTIPLE CKT 1	28.8/33.3	3.8	41/47	45/ 50
		6.0/8.0	1/60	2 - 4.0	MULTIPLE CKT 2	28.8/33.3	0.0	36/42	40/ 45
		6.0/8.0	1/60	2 - 4.0	MULTIPLE CKT 3	28.8/33.3	0.0	36/42	40/ 45
	RXBH-24A25C	18.0/24.0	3/60	6-4.0	SINGLE	50.0/57.8	3.8	68/77	70/ 80
	RXBH-24A25C (4-ton only)	9.0/12.0	3/60	3 - 4.0	MULTIPLE CKT 1	25.0/28.9	3.8	36/41	40/ 45
9.0/12.0		3/60	3 - 4.0	MULTIPLE CKT 2	25.0/28.9	0.0	32/37	35/ 40	

Addendum for High kW Electric Heat Electrical Data on (-)HLA/(-)HLL - continued

NORMAL COOLING CAPACITY TONS CABINET SIZE	Model No.	HEATER kW 208/240V	PH/HZ	NO. ELEMENTS - kW PER	TYPE SUPPLY CIRCUIT		CIRCUIT AMPS.	MOTOR AMPACITY	MINIMUM CIRCUIT AMPACITY	MAXIMUM CIRCUIT PROTECTION
					SINGLE CIRCUIT	MULTIPLE CIRCUIT				
(-)HLA/(-)HLL 4 & 5 24	RXBH-24A25J	18.0/24.0	1/60	6-4.0	SINGLE		86.4/99.9	4.6	114/131	125/ 150
	RXBH-24A25J	6.0/8.0	1/60	2 - 4.0	MULTIPLE CKT 1		28.8/33.3	4.6	42/48	45/ 50
		6.0/8.0	1/60	2 - 4.0	MULTIPLE CKT 2		28.8/33.3	0	36/42	40/ 45
		6.0/8.0	1/60	2 - 4.0	MULTIPLE CKT 3		28.8/33.3	0	36/42	40/ 45
	RXBH-24A30J	21.6/28.8	1/60	6-4.8	SINGLE		103.8/120	4.6	136/156	150/ 175
	RXBH-24A30J (5-ton only)	7.2/9.6	1/60	2 - 4.8	MULTIPLE CKT 1		34.6/40.0	4.6	49/56	50/ 60
		7.2/9.6	1/60	2 - 4.8	MULTIPLE CKT 2		34.6/40.0	0	44/50	45/ 50
		7.2/9.6	1/60	2 - 4.8	MULTIPLE CKT 3		34.6/40.0	0	44/50	45/ 50
	RXBH-24A25C	18.0/24.0	3/60	6-4.0	SINGLE		50.0/57.8	4.6	69/78	70/ 80
	RXBH-24A25C	9.0/12.0	3/60	3 - 4.0	MULTIPLE CKT 1		25.0/28.9	4.6	37/42	40/ 45
		9.0/12.0	3/60	3 - 4.0	MULTIPLE CKT 2		25.0/28.9	0	32/37	35/ 40
	RXBH-24A30C	21.6/28.8	3/60	6-4.8	SINGLE		60.0/69.4	4.6	81/93	90/ 100
RXBH-24A30C (5-ton only)	10.8/14.4	3/60	3 - 4.8	MULTIPLE CKT 1		30.0/34.7	4.6	44/50	45/ 50	
	10.8/14.4	3/60	3 - 4.8	MULTIPLE CKT 2		30.0/34.7	0	38/44	40/ 45	

High kW Electric Heat Electrical Data: (-)HKA, (-)HKL

NORMAL COOLING CAPACITY TONS CABINET SIZE	Model No.	HEATER kW 208/240V	PH/HZ	NO. ELEMENTS - kW PER	TYPE SUPPLY CIRCUIT		CIRCUIT AMPS.	MOTOR AMPACITY	MINIMUM CIRCUIT AMPACITY	MAXIMUM CIRCUIT PROTECTION
					SINGLE CIRCUIT	MULTIPLE CIRCUIT				
(-)HKA/(-)HKL 1-1/2 & 2 17	RXBH-17A13J	9.4/12.5	1/60	3-4.17	SINGLE		45.1/52.1	2.2	60/68	60/ 70
	RXBH-17A13J	3.1/4.2	1/60	1-4.17	MULTIPLE CKT 1		15.0/17.4	2.2	22/25	25/ 25
		6.3/8.3	1/60	2-4.17	MULTIPLE CKT 2		30.1/34.7	0	38/44	40/ 45
RXBH-17A13C	9.4/12.5	3/60	3 - 4.17	SINGLE		26.1/30.1	2.2	36/41	40/ 45	
(-)HKA/(-)HKL 2-1/2 & 3 17	RXBH-17A13J	9.4/12.5	1/60	3-4.17	SINGLE		45.1/52.1	3.1	61/69	70/ 70
	RXBH-17A13J	3.1/4.2	1/60	1-4.17	MULTIPLE CKT 1		15.0/17.4	3.1	23/26	25/ 30
		6.3/8.3	1/60	2-4.17	MULTIPLE CKT 2		30.1/34.7	0	38/44	40/ 45
	RXBH-17A18J	12.8/17.0	1/60	3-5.68	SINGLE		61.6/70.8	3.1	81/93	90/ 100
	RXBH-17A18J	4.3/5.7	1/60	1-5.68	MULTIPLE CKT 1		20.5/23.6	3.1	30/34	30/ 35
		8.5/11.3	1/60	2 - 5.68	MULTIPLE CKT 2		41.1/47.2	0	52/59	60/ 60
RXBH-17A13C	9.4/12.5	3/60	3 - 4.17	SINGLE		26.1/30.1	3.1	37/42	40/ 45	
RXBH-17A18C	12.8/17.0	3/60	3-5.68	SINGLE		35.5/41.0	3.1	49/56	50/ 60	
(-)HKA/(-)HKL 3-1/2 & 4 21	RXBH-24A25J	18.0/24.0	1/60	6-4.0	SINGLE		86.4/99.9	4.0	113/130	125/ 150
	RXBH-24A25J (4-ton only)	6.0/8.0	1/60	2 - 4.0	MULTIPLE CKT 1		28.8/33.3	4.0	42/47	45/ 50
		6.0/8.0	1/60	2 - 4.0	MULTIPLE CKT 2		28.8/33.3	0.0	36/42	40/ 45
		6.0/8.0	1/60	2 - 4.0	MULTIPLE CKT 3		28.8/33.3	0.0	36/42	40/ 45
	RXBH-24A25C	18.0/24.0	3/60	6-4.0	SINGLE		50.0/57.8	4.0	68/78	70/ 80
RXBH-24A25C (4-ton only)	9.0/12.0	3/60	3 - 4.0	MULTIPLE CKT 1		25.0/28.9	4.0	37/42	40/ 45	
	9.0/12.0	3/60	3 - 4.0	MULTIPLE CKT 2		25.0/28.9	0.0	32/37	35/ 40	
(-)HKA/(-)HKL 4 & 5 24	RXBH-24A25J	18.0/24.0	1/60	6-4.0	SINGLE		86.4/99.9	4.4	114/131	125/ 150
	RXBH-24A25J	6.0/8.0	1/60	2 - 4.0	MULTIPLE CKT 1		28.8/33.3	4.4	42/48	45/ 50
		6.0/8.0	1/60	2 - 4.0	MULTIPLE CKT 2		28.8/33.3	0	36/42	40/ 45
		6.0/8.0	1/60	2 - 4.0	MULTIPLE CKT 3		28.8/33.3	0	36/42	40/ 45
	RXBH-24A30J	21.6/28.8	1/60	6-4.8	SINGLE		103.8/120.	4.4	136/156	150/ 175
	RXBH-24A30J (5-ton only)	7.2/9.6	1/60	2 - 4.8	MULTIPLE CKT 1		34.6/40.0	4.4	49/56	50/ 60
		7.2/9.6	1/60	2 - 4.8	MULTIPLE CKT 2		34.6/40.0	0	44/50	45/ 50
		7.2/9.6	1/60	2 - 4.8	MULTIPLE CKT 3		34.6/40.0	0	44/50	45/ 50
	RXBH-24A25C	18.0/24.0	3/60	6-4.0	SINGLE		50.0/57.8	4.4	68/78	70/ 80
	RXBH-24A25C	9.0/12.0	3/60	3 - 4.0	MULTIPLE CKT 1		25.0/28.9	4.4	37/42	40/ 45
		9.0/12.0	3/60	3 - 4.0	MULTIPLE CKT 2		25.0/28.9	0	32/37	35/ 40
	RXBH-24A30C	21.6/28.8	3/60	6-4.8	SINGLE		60.0/69.4	4.4	81/93	90/ 100
RXBH-24A30C (5-ton only)	10.8/14.4	3/60	3 - 4.8	MULTIPLE CKT 1		30.0/34.7	4.4	43/49	45/ 50	
	10.8/14.4	3/60	3 - 4.8	MULTIPLE CKT 2		30.0/34.7	0	38/44	40/ 45	

Addendum for High kW Electric Heat Electrical Data on (-)HPL

(-)HPL 5 24	RXBH-24A30J	21.6/28.8	1/60	6-4.8	SINGLE		103.8/120.	4.9	136/156	150/ 175
	RXBH-24A30J (5-ton only)	7.2/9.6	1/60	2 - 4.8	MULTIPLE CKT 1		34.6/40.0	4.9	49/56	50/ 60
		7.2/9.6	1/60	2 - 4.8	MULTIPLE CKT 2		34.6/40.0	0	44/50	45/ 50
		7.2/9.6	1/60	2 - 4.8	MULTIPLE CKT 3		34.6/40.0	0	44/50	45/ 50