



# Packaged Cooling Convertible 2-5 Tons



**4TCY5**

**Table PK-1-A — 4TCY5 - Gold 15 - Convertible Packaged Cooling - R-410A**

Model Number	Cooling Capacity (Btuh)	SEER/EER	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4TCY5 – 208-230/1/60</b>							
4TCY5024A1000A	-	15.00/12.00	-	-	-	-	36 x 42 x 49
4TCY5030A1000A	-	15.00/12.00	-	-	-	-	38 x 42 x 49
4TCY5036A1000A	-	15.00/12.00	-	-	-	-	38 x 42 x 49
4TCY5042A1000A	-	15.00/12.00	-	-	-	-	38 x 45 x 59
4TCY5048A1000A	-	15.00/12.00	-	-	-	-	42 x 45 x 59
4TCY5060A1000A	-	15.00/11.40	-	-	-	-	42 x 45 x 59



**4TCY4**

**Table PK-1-B — 4TCY4 - Gold 14 - Convertible Packaged Cooling - R-410A**

Model Number	Cooling Capacity (Btuh)	SEER/EER	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4TCY4 – 208-230/1/60</b>							
4TCY4024A1000B	23,400	14.00/12.00	444	16.5	25	68	36 x 42 x 49
4TCY4030A1000B	30,000	14.00/12.00	444	19.1	30	71	38 x 42 x 49
4TCY4036B1000B	38,000	14.20/12.00	450	24.6	40	69	38 x 42 x 49
4TCY4042B1000B	42,000	14.25/12.00	607	31.6	50	74	38 x 45 x 59
4TCY4048B1000B	50,000	14.20/12.00	607	35.4	50	72	42 x 45 x 59
4TCY4060A1000B	60,000	14.00/12.00	612	42.3	60	76	42 x 45 x 59
<b>4TCY4 – 208-230/3/60</b>							
4TCY4036B3000A	38,000	14.20/12.00	450	19.8	30	69	38 x 42 x 49
4TCY4048B3000A	48,500	14.20/11.90	607	26.4	40	72	38 x 45 x 59
4TCY4060A3000B	60,000	14.00/12.00	612	30.6	45	76	42 x 45 x 59

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

For complete equipment / combination selections, installation instructions and warranty information, please refer to Product Data/Ratings and/or Installers Guides and Limited Warranty Handbooks.

# Packaged Cooling Convertible 2-5 Tons

**Table PK-2-A — Features**

	<b>4TCY5 2-5</b>	<b>4TCY4 2-5</b>
• SEER up to .....	15.00	14.25
• Exclusive <b>Duration™</b> high efficiency compressor with internal overload protection.....	✓	✓
• Factory supplied charge.....	R-410A	R-410A
• Composite <b>Vortica®</b> indoor blower.....	✓	✓
• High efficiency ECM indoor blower motor with <b>Comfort-R™</b> airflow system.....	✓	✓
• All aluminum <b>Spine Fin™</b> outdoor coil.....	✓	✓
• Swept-blade outdoor fan for quiet operation .....	✓	✓
• Architecturally integrated louvers and corner guards.....	✓	✓
• Polyslate gray cabinet .....	✓	✓
• Single stage cool.....	2-3½	✓
• Two stage cooling.....	4,5	—
• High pressure cutout .....	✓	✓
• Low pressure cutout.....	✓	✓
• Liquid line drier - factory installed .....	✓	✓
• Non-bleed expansion valves on indoor coil.....	✓	✓
• Pressure taps, including liquid line taps, easily accessed and protected inside compressor compartment .....	✓	✓
• Right side electrical service access for high and low voltage connections.....	✓	✓
• Rugged steel basepan features deep drawn duct connections .....	✓	✓
• Steeply sloped composite drainpan .....	✓	✓
• Ships in horizontal configuration and converts quickly for downflow .....	✓	✓
• Copper tube, aluminum fin indoor coil .....	3,4,& 5	✓
• All aluminum indoor coil.....	2, 2½, 3½	—
• All models are certified to UL 1995.....	✓	✓
• <b>10-year compressor, 10-year outdoor coil &amp; all other functional parts registered limited warranty (Residential Use)①</b> .....	✓	✓
• <b>Extended warranties available</b> .....	✓	✓

① Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 800-554-8005; otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ASDealerNet.com.

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

**Table PK-3-A — Accessories**


Model Number	Description	Shipping Weight	4TCY5 2-5	4TCY4 2-5
BAYACCDOR1A	Hinged Filter Access Door <sup>①</sup> .....		2-3	2-3
BAYACCDOR2A	Hinged Filter Access Door <sup>①</sup> .....		3½-5	3½-5
BAYADAP050A	Adapter Curb (Cabinet A/B) .....		2-3	2-3
BAYADAP051A	Adapter Curb (Cabinet C).....		2-3	2-3
BAYADAP052A	Adapter Curb (Cabinet A/B) .....		3½-5	3½-5
BAYADAP053A	Adapter Curb (Cabinet C).....		3½-5	3½-5
BAYADAP054A	Adapter Curb (Cabinet D).....		3½-5	3½-5
BAYASCT001	Anti-Short Cycle Timer <sup>④</sup> .....		✓	✓
BAYCCHT101A	Crankcase Heater (230V) (Reciprocating) .....		—	2-2½
BAYCCHT102A	Crankcase Heater (230V) (Scroll) .....		3½-5	3½-5
BAYCCHT103A	Crankcase Heater (230V) (Scroll) .....		2-3	3
BAYCOVR112A	12" Duct Shroud (Covers Horizontal Ducts) <sup>⑤</sup> .....		2-5	2-5
BAYCOVR118A	18" Duct Shroud (Covers Horizontal Ducts) <sup>⑤</sup> .....		2-5	2-5
BAYCURB050A	Flat Roof Full Perimeter Curb (Insulated) .....	74	2-3	2
BAYCURB051A	Flat Roof Full Perimeter Curb (Insulated) .....	74	3½-5	3½-5
BAYDMPR101A	2-Position Motorized Fresh Air Damper <sup>①⑥⑦⑧⑨</sup> .....		2-3	2-3
BAYDMPR102A	2-Position Motorized Fresh Air Damper <sup>①⑥⑦⑧⑨</sup> .....		3½-5	3½-5
BAYECON101A	Economizer with Barometric Relief (Downflow) <sup>①②③⑨⑩</sup> .....	50	2-3	2-3
BAYECON102A	Economizer with Barometric Relief (Downflow) <sup>①②③⑨⑩</sup> .....	65	3½-5	3½-5
BAYECON104AB	Economizer with Barometric Relief (Downflow) <sup>①②③⑨⑩</sup> .....	65	4-5	—
BAYECON200A	Economizer (Horizontal) <sup>①②③⑥</sup> .....	85	2-3	2-3
BAYECON201A	Economizer (Horizontal) <sup>①②③⑥</sup> .....	85	3½	3½-5
BAYECON204A	Economizer (Horizontal) <sup>①②③⑥</sup> .....	85	4-5	2-5
BAYENTH001A	Enthalpy Control Kit <sup>②</sup> .....	2	✓	✓
BAYEXMK001A	Extreme Conditions Mounting Kit (Used on BAYCURB & BAYADAP).....		✓	✓
BAYEXMK002B	Extreme Conditions Mounting Kit (Used on BAYUTIL) .....		✓	✓
BAYEXMK003A	Extreme Conditions Mounting Kit (Used on Slab Mounts).....		✓	✓
BAYFLTR101C	1-2" Filter Frame (requires one 20x25 filter which is not included) <sup>①</sup> .....	6	2-3	2-3
BAYFLTR201C	1-2" Filter Frame (requires one 20x20 and one 20x18 filter which are not included) <sup>①</sup> .....	6	3½-5	3½-5
BAYLIFT002B	Lifting Lug Kit .....	5	✓	✓
BAYLOAM011A	Evaporator Defrost Control Kit .....		✓	✓
BAYLOAM105A	Low Ambient Control Kit .....	5	✓	✓
BAYOSAH001A	Manual Fresh Air Damper <sup>①</sup> .....	6	2-3	2-3
BAYOSAH002A	Manual Fresh Air Damper <sup>①</sup> .....	8	3½-5	3½-5
BAYQSTK300A	Start Kit .....		1 Phase Only	1 Phase Only
BAYSQRD001A	16" Round Duct Adapter <sup>⑩</sup> .....	5	2-3	2-3
BAYSQRD002A	18" Round Duct Adapter <sup>⑩</sup> .....	3	2-5	2-5
BAYUTIL101B	Roof Curb Utility Extension Kit .....		2-3	2-3
BAYUTIL102B	Roof Curb Utility Extension Kit .....		3½-5	3½-5
4BAYUV101A	21" Retrofit UVC Lamp Kit.....	5	2-3	2-3
BAYUV102A	33" Retrofit UVC Lamp Kit.....	5	3½-5	3½-5

- ① Must use filter frame when economizer/fresh air kit is used.
- ② Dry bulb control standard with economizer.
- ③ 2-Stage cooling control required when using economizer.
- ④ Do not use with electronic thermostats.
- ⑤ BAYCOVR112,118A will not cover BAYSQRD002A applications.
- ⑥ Does not contain barometric relief.
- ⑦ Max fresh air - 25%.
- ⑧ For non-continuous fan gas-heating applications, the damper opens only when the OD ambient is above 50° F.
- ⑨ It is the designer/engineer's responsibility to review product specifications prior to equipment selection to insure optimal performance and compliance to codes.
- ⑩ Temperature of mixed air entering the heat exchanger is monitored and fresh air intake may be reduced under certain conditions.
- ⑪ BAYACCDOR1A requires BAYFLTR101B & BAYACCDOR2A requires BAYFLTR201B. They are not backward compatible to BAYFLTR101/201A.

EXISTING CURB	NEW UNIT 4TCY4/5	USE BAYADAP0**A
BAYCURB030,38A	024-036	50
BAYCURB030,38A	042-060	52
BAYCURB033A	024-036	51
BAYCURB033A	024-060	53
BAYCURB034A	042-060	54

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**


# Packaged Cooling Convertible 2-5 Tons



**4TCX3**  
(3-Phase Only)

**Table PK-4-A — 4TCX3 - Gold 13 - Convertible Packaged Cooling - R-410A**


Model Number	Cooling Capacity (Btuh)	SEER/EER	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4TCX3 – 208-230/3/60</b>							
4TCX3036A3000B	36,000	13.20/11.00	450	18.2	30	72	36 x 42 x 49
4TCX3048A3000B	46,500	13.00/11.00	607	23.6	35	72	38 x 45 x 59
4TCX3060A3000B	60,000	13.20/11.00	610	31.7	50	72	40 x 45 x 59
<b>4TCX3 – 460/3/60</b>							
4TCX3036A4000B	36,000	13.20/11.00	450	8.7	15	72	36 x 42 x 49
4TCX3048A4000A	46,500	13.00/11.00	607	11.7	15	72	38 x 45 x 59
4TCX3060A4000B	60,000	13.20/11.00	610	19.5	25	72	40 x 45 x 59



**4TCC4**

**Table PK-4-B— 4TCC4 - Silver 14 - Convertible Packaged Cooling - R-410A**

Model Number	Cooling Capacity (Btuh)	SEER/EER	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4TCC4 – 208-230/1/60</b>							
4TCC4024A1000A	24,600	14.00/12.00	432	19.1	30	67	36 x 42 x 49
4TCC4030A1000A	28,200	14.00/12.00	451	22.6	35	69	36 x 42 x 49
4TCC4036A1000A	37,000	14.00/12.00	453	24.5	40	69	38 x 42 x 49
4TCC4042A1000A	40,500	14.00/12.00	561	28.5	45	75	36 x 45 x 59
4TCC4048A1000A	46,500	14.00/11.50	557	32.0	50	73	40 x 45 x 59
4TCC4060A1000A	58,000	14.00/11.50	586	39.1	60	73	40 x 45 x 59



**4TCC3**  
(3-Phase Only)

**Table PK-4-C — 4TCC3 - Silver 13 - Convertible Packaged Cooling - R-410A**

Model Number	Cooling Capacity (Btuh)	SEER/EER	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4TCC3 – 208-230/3/60</b>							
4TCC3036A3000B	35,000	13.00/11.00	450	18.2	30	76	36 x 42 x 49
4TCC3048A3000B	46,500	13.00/11.00	607	23.6	35	80	38 x 45 x 59
4TCC3060A3000B	58,000	13.00/11.00	610	31.7	50	79	40 x 45 x 59
<b>4TCC3 – 460/3/60</b>							
4TCC3036A4000B	35,000	13.00/11.00	450	8.7	15	76	36 x 42 x 49
4TCC3048A4000B	46,500	13.00/11.00	607	11.7	15	80	38 x 45 x 59
4TCC3060A4000B	58,000	13.00/11.00	610	19.5	25	79	40 x 45 x 59

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

# Packaged Cooling Convertible 2-5 Tons

**Table PK-5-A — Features**

	<b>4TCX3 3-5</b>	<b>4TCC4 2-5</b>	<b>4TCC3 3-5</b>
• SEER up to.....	13.20	14.00	13.00
• Exclusive <b>Duration™</b> high efficiency compressor with internal overload protection.....	✓	✓	✓
• Factory supplied charge.....	R-410A	R-410A	R-410A
• Composite <b>Vortica®</b> indoor blower.....	✓	✓	✓
• Direct drive multi-speed indoor blower motors.....	✓	✓	—
• All aluminum <b>Spine Fin™</b> outdoor coil.....	✓	✓	✓
• Swept-blade outdoor fan for quiet operation.....	✓	✓	✓
• Architecturally integrated louvers and corner guards.....	✓	—	✓
• All steel louvers.....	—	✓	✓
• Polyslate gray cabinet.....	✓	✓	✓
• Single stage cool .....	✓	✓	✓
• High pressure cutout .....	✓	✓	✓
• Low pressure cutout.....	3-Phase Only	✓	3-Phase Only
• Liquid line drier - factory installed .....	✓	✓	✓
• Non-bleed expansion valves on indoor coil.....	✓	✓	✓
• Pressure taps, including liquid line taps, easily accessed and protected inside compressor compartment.....	✓	✓	✓
• Right side electrical service access for high and low voltage connections. ....	✓	✓	✓
• Rugged steel basepan features deep drawn duct connections.....	✓	✓	✓
• Steeply sloped composite drainpan.....	✓	✓	✓
• Ships in horizontal configuration and converts quickly for downflow .....	✓	✓	✓
• Copper tube, aluminum fin indoor coil .....	✓	5	✓
• All aluminum indoor coil.....	—	2-4	—
• All models are certified to UL 1995 .....	✓	✓	✓
• <b>10-year compressor, 10-year outdoor coil &amp; all other functional parts registered limited warranty (Residential Use)①</b> .....	✓	✓	✓
• <b>Extended warranties available</b> .....	✓	✓	✓

① Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 800-554-8005; otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ASDealerNet.com.

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

# Packaged Cooling Convertible 2-5 Tons

**Table PK-6-A — Accessories**

Model Number	Description	Shipping Weight	4TCX3 3-5	4TCC4 2-5	4TCC3 3-5
BAYACCDOR1A	Hinged Filter Access Door <sup>⑩</sup> .....		3	2-3	3
BAYACCDOR2A	Hinged Filter Access Door <sup>⑩</sup> .....		4-5	3½-5	4-5
BAYADAP050A	Adapter Curb (Cabinet A/B) .....		3	2-3	3
BAYADAP051A	Adapter Curb (Cabinet C) .....		3	2-3	3
BAYADAP052A	Adapter Curb (Cabinet A/B) .....		4-5	3½-5	4-5
BAYADAP053A	Adapter Curb (Cabinet C) .....		4-5	3½-5	4-5
BAYADAP054A	Adapter Curb (Cabinet D) .....		4-5	3½-5	4-5
BAYASCT001	Anti-Short Cycle Timer <sup>④</sup> .....		✓	—	✓
BAYCCHT102A	Crankcase Heater (230V) (Scroll) .....		4-5	3½-5	4-5
BAYCCHT103A	Crankcase Heater (230V) (Scroll) .....		3	2-3	3
BAYCCHT404B	Crankcase Heater (460V) (Scroll) .....		4-5	—	4-5
BAYCCHT405A	Crankcase Heater (460V) (Scroll) .....		3	—	3
BAYCOVR112A	12" Duct Shroud (Covers Horizontal Ducts) <sup>⑤</sup> .....		3-5	2-5	3-5
BAYCOVR118A	18" Duct Shroud (Covers Horizontal Ducts) <sup>⑤</sup> .....		3-5	2-5	3-5
BAYCURB050A	Flat Roof Full Perimeter Curb (Insulated) .....74.....	74	3	2-3	3
BAYCURB051A	Flat Roof Full Perimeter Curb (Insulated) .....74.....	74	4-5	3½-5	4-5
BAYDMPR101A	2-Position Motorized Fresh Air Damper <sup>①⑥⑦⑧⑨</sup> .....		3	2-3	3
BAYDMPR102A	2-Position Motorized Fresh Air Damper <sup>①⑥⑦⑧⑨</sup> .....		4-5	3½-5	4-5
BAYECON101A	Economizer with Barometric Relief (Downflow) <sup>①②③④⑤⑩</sup> .....50.....	50	3	2-3	3
BAYECON102A	Economizer with Barometric Relief (Downflow) <sup>①②③④⑤⑩</sup> .....65.....	65	4-5	3½-5	4-5
BAYECON200A	Economizer (Horizontal) <sup>①②③⑥</sup> .....85.....	85	3	2-3	3
BAYECON201A	Economizer (Horizontal) <sup>①②③⑥</sup> .....85.....	85	4-5	3½-5	4-5
BAYECON204A	Economizer (Horizontal) <sup>①②③⑥</sup> .....85.....	85	3-5	2-5	3-5
BAYENTH001A	Enthalpy Control Kit <sup>②</sup> .....	2	✓	✓	✓
BAYEXMK001A	Extreme Conditions Mounting Kit (Used on BAYCURB & BAYADAP).....		✓	✓	✓
BAYEXMK002B	Extreme Conditions Mounting Kit (Used on BAYUTIL) .....		✓	✓	✓
BAYEXMK003A	Extreme Conditions Mounting Kit (Used on Slab Mounts) .....		✓	✓	✓
BAYFLTR101C	1-2" Filter Frame (requires one 20x25 filter which is not included) <sup>①</sup> .....6.....	6	3	2-3	3
BAYFLTR201C	1-2" Filter Frame (requires one 20x20 and one 20x18 filter which are not included) <sup>①</sup> .....6.....	6	4-5	3½-5	4-5
BAYLIFT002B	Lifting Lug Kit .....	5	✓	✓	✓
BAYLOAM011A	Evaporator Defrost Control Kit .....		✓	✓	✓
BAYLOAM105A	Low Ambient Control Kit.....5.....	5	✓	✓	✓
BAYLOAM107A	Low Ambient Control Kit.....5.....	5	—	✓	—
BAYOSAH001A	Manual Fresh Air Damper <sup>①</sup> .....6.....	6	3	2-3	3
BAYOSAH002A	Manual Fresh Air Damper <sup>①</sup> .....8.....	8	4-5	3½-5	4-5
BAYQSTK300A	Start Kit .....		—	✓	—
BAYSQRD001A	16" Round Duct Adapter <sup>⑩</sup> .....5.....	5	3	2-3	3
BAYSQRD002A	18" Round Duct Adapter <sup>⑩</sup> .....3.....	3	3-5	2-5	3-5
BAYUTIL101B	Roof Curb Utility Extension Kit .....		3	2-3	3
BAYUTIL102B	Roof Curb Utility Extension Kit .....		4-5	3½-5	4-5
BAYUV101A	21" Retrofit UVC Lamp Kit.....5.....	5	3	2-3	3
BAYUV102A	33" Retrofit UVC Lamp Kit.....5.....	5	4-5	3½-5	4-5


- ① Must use filter frame when economizer/fresh air kit is used.
- ② Dry bulb control standard with economizer.
- ③ 2-Stage cooling control required when using economizer.
- ④ Do not use with electronic thermostats.
- ⑤ BAYCOVR112,118A will not cover BAYSQRD002A applications.
- ⑥ Does not contain barometric relief.
- ⑦ Max fresh air - 25%.
- ⑧ For non-continuous fan gas-heating applications, the damper opens only when the OD ambient is above 50° F.
- ⑨ It is the designer/engineer's responsibility to review product specifications prior to equipment selection to insure optimal performance and compliance to codes.
- ⑩ Temperature of mixed air entering the heat exchanger is monitored and fresh air intake may be reduced under certain conditions.
- ⑪ BAYACCDOR1A requires BAYFLTR101B & BAYACCDOR2A requires BAYFLTR201B. They are not backward compatible to BAYFLTR101/201A.

EXISTING CURB	NEW UNIT 4TC**	USE BAYADAP0**A
BAYCURB030,38A	024-036	50
BAYCURB030,38A	042-060	52
BAYCURB033A	024-036	51
BAYCURB033A	024-060	53
BAYCURB034A	042-060	54

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

For complete equipment / combination selections, installation instructions and warranty information, please refer to Product Data/Ratings and/or Installers Guides and Limited Warranty Handbooks.


# Packaged Heat Pump/Dual Fuel Convertible 2-5 Tons



**4WCZ6**

**Table PK-7-A — 4WCZ6 - Platinum 16 - Convertible Packaged Heat Pump - R-410A**


Model Number	Capacity	SEER	EER High/Low	HSPF	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4WCZ6 – 208-230/1/60</b>									
4WCZ6036B1000A	36,000	16.00	12.20/17.45	8.30	468	24.3	35	70	38 x 42 x 49
4WCZ6048B1000A	47,500	16.00	12.00/17.50	8.50	607	34.2	50	72	42 x 45 x 59
4WCZ6060B1000A	57,000	15.00	11.50/15.90	8.30	623	42.0	60	74	42 x 45 x 59
<b>4WCZ6 – 208-230/3/60</b>									
4WCZ6036B3000A	36,000	16.00	12.20/17.45	8.30	468	19.7	30	70	38 x 42 x 49
4WCZ6048B3000A	47,500	16.00	12.00/17.50	8.50	607	25.2	35	72	42 x 45 x 59
4WCZ6060B3000A	57,000	15.00	11.50/15.90	8.30	623	30.0	45	74	42 x 45 x 59
<b>4WCZ6 – 460/3/60</b>									
4WCZ6036B4000A	36,000	16.00	12.20/17.45	8.30	468	11.9	15	70	38 x 42 x 49
4WCZ6048B4000A	47,500	16.00	12.00/17.50	8.50	607	15.3	20	72	42 x 45 x 59
4WCZ6060B4000A	57,000	15.00	11.50/15.90	8.30	623	17.0	20	74	42 x 45 x 59



**4DCZ6**

**Table PK-7-B — 4DCZ6 - Platinum 16 - Convertible Packaged Heat Pump/Dual Fuel - R-410A**

Model Number	Cooling Capacity (BTUH)	Gas Capacity Heating Output (1 Stg./2 Stg.)	SEER/EER	HSPF	AFUE(%)	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4DCZ6 – 208-230/1/60</b>										
4DCZ6036C1070A	36,000	45,000/57,000	16.00 /12.20	8.30	81.0	488	24.3	35	70	38 x 42 x 49
4DCZ6048C1090A	47,500	58,000/73,000	16.00 /12.00	8.50	81.0	665	34.2	50	72	42 x 45 x 59
4DCZ6060C1115A	57,000	75,000/93,000	15.00 /11.50	8.30	81.0	676	42.0	60	74	42 x 45 x 59
<b>4DCZ6 – 208-230/3/60</b>										
4DCZ6036B3075A	36,000	48,400/60,000	16.00 /12.20	8.30	79.5	488	19.7	30	70	38 x 42 x 49
4DCZ6048B3096A	47,500	62,000/77,000	16.00 /12.00	8.50	80.0	665	25.2	35	72	42 x 45 x 59
4DCZ6060B3120A	57,000	77,500/96,000	15.00 /11.50	8.30	80.0	676	30.0	45	74	42 x 45 x 59



**4DCY4**

**Table PK-7-C — 4DCY4 - Gold 14 - Convertible Packaged Heat Pump/Dual Fuel - R-410A**

Model Number	Cooling Capacity (BTUH)	Gas Capacity Heating Output (1 Stg./2 Stg.)	SEER/EER	HSPF	AFUE(%)	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4DCY4 – 208-230/1/60</b>										
4DCY4024C1060A	23,600	39,000/49,000	14.00/12.00	8.00	81.0	481	16.1	25	68	36 x 42 x 49
4DCY4030C1070A	30,000	45,000/57,000	14.25/12.00	8.00	81.0	481	19.1	30	76	36 x 42 x 49
4DCY4036C1070A	37,000	45,000/57,000	14.00/12.00	8.00	81.0	488	24.6	40	69	38 x 42 x 49
4DCY4042C1090A	42,000	58,000/73,000	14.00/12.00	8.00	81.0	653	30.8	45	74	38 x 45 x 59
4DCY4048C1090A	47,500	58,000/73,000	14.00/12.00	8.00	81.0	653	33.9	50	73	38 x 45 x 59
4DCY4060C1115A	58,000	75,000/93,000	14.00/12.00	8.00	81.0	676	39.9	60	76	42 x 45 x 59
<b>4DCY4 – 208-230/3/60</b>										
4DCY4036B3075A	36,000	48,400/60,000	14.00/11.40	8.00	79.5	488	19.8	30	69	38 x 42 x 49
4DCY4048A3096C	47,000	62,000/77,000	14.00/10.80	8.00	80.0	653	26.4	40	73	38 x 45 x 59
4DCY4060A3120C	57,500	77,500/96,000	14.00/11.50	8.00	80.0	676	30.6	60	76	42 x 45 x 59

For dimensional/outline drawings, please refer to Product Data.

For information on Roof Curbs, please refer to the Accessories/Information Tab.

For complete equipment / combination selections, installation instructions and warranty information, please refer to Product Data/Ratings and/or Installers Guides and Limited Warranty Handbooks.



# Packaged Heat Pump/Dual Fuel Convertible 2-5 Tons

**Table PK-8-A — Features**

	4WCZ6 3-5	4DCZ6 3-5	4DCY4 2-5
• SEER up to.....	16.00	16.00	14.25
• HSPF up to.....	8.50	8.50	8.00
• Exclusive <b>Duration™</b> high efficiency compressor with internal overload protection.....	✓	✓	✓
• Factory supplied charge.....	R-410A	R-410A	R-410A
• Composite <b>Vortica®</b> indoor blower.....	✓	✓	✓
• High efficiency ECM indoor blower motor with <b>Comfort-R™</b> airflow system.....	✓	✓	✓
• All aluminum <b>Spine Fin™</b> outdoor coil.....	✓	✓	✓
• Swept-blade outdoor fan for quiet operation.....	✓	✓	✓
• Architecturally integrated louvers and corner guards.....	✓	✓	✓
• Polyslate gray cabinet.....	✓	✓	✓
• Stainless steel heat exchanger and burners.....	—	✓	✓
• Single stage heating and cool.....	—	—	✓
• 2-stage heating and cooling.....	✓	✓	—
• 2-stage gas.....	—	✓	✓
• Start kit - factory installed (single phase only).....	—	—	2 & 2½
• High pressure cutout.....	✓	✓	✓
• Low pressure cutout.....	✓	✓	✓
• Liquid line drier - factory installed.....	✓	✓	✓
• Non-bleed expansion valves on indoor and outdoor coils.....	✓	✓	✓
• Pressure taps, including liquid line taps, easily accessed and protected inside compressor compartment.....	✓	✓	✓
• Right side electrical service access for high and low voltage connections.....	✓	✓	✓
• Rugged steel basepan features deep drawn duct connections.....	✓	✓	✓
• Steeply sloped composite drainpan.....	✓	✓	✓
• Ships in horizontal configuration and converts quickly for downflow.....	✓	✓	✓
• Copper tube, aluminum fin indoor coil.....	✓	✓	✓
• All models are certified to UL 1995.....	✓	✓	✓
• <b>20-year heat exchanger, 12-year compressor, 10-year outdoor coil, &amp; 10-year all other functional parts registered limited warranty (Residential Use)①</b> .....	—	✓	—
• <b>20-year heat exchanger, 10-year compressor, 10-year outdoor coil, &amp; 10-year all other functional parts registered limited warranty (Residential Use)①</b> .....	—	—	✓
• <b>12-year compressor, 10-year outdoor coil, &amp; 10-year all other functional parts registered limited warranty (Residential Use)①</b> .....	✓	—	—
• <b>Extended Warranties Available</b> .....	✓	✓	✓

① Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at [americanstandardair.com](http://americanstandardair.com) or by phone at 800-554-8005; otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on [ASDealerNet.com](http://ASDealerNet.com).

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**



# Packaged Heat Pump/Dual Fuel Convertible 2-5 Tons

Table PK-9-A — Accessories			4WCZ6 3-5	4DCZ6 3-5	4DCY4 2-5
Model Number	Description	Shipping Weight			
BAYACCDOR1A	Hinged Filter Access Door <sup>®</sup> .....		3	3	2-3
BAYACCDOR2A	Hinged Filter Access Door <sup>®</sup> .....		4-5	4-5	3½-5
BAYADAP050A	Adapter Curb (Cabinet A/B).....		3	3	2-3
BAYADAP051A	Adapter Curb (Cabinet C).....		3	3	2-3
BAYADAP052A	Adapter Curb (Cabinet A/B).....		4-5	4-5	3½-5
BAYADAP053A	Adapter Curb (Cabinet C).....		4-5	4-5	3½-5
BAYADAP054A	Adapter Curb (Cabinet D).....		4-5	4-5	3½-5
BAYASCT001	Anti-Short Cycle Timer <sup>④</sup> .....		✓	✓	✓
BAYCCHT101A	Crankcase Heater (230V) (Reciprocating).....		—	—	2-2½
BAYCCHT102A	Crankcase Heater (230V) (Scroll).....		4,5	4,5	3½-5
BAYCCHT103A	Crankcase Heater (230V) (Scroll).....		3	3	3
BAYCCHT404B	Crankcase Heater (460V) (Scroll).....		4,5	4,5	—
BATCCHT405A	Crankcase Heater (460V) (Scroll).....		3	3	—
BAYCOVR112A	12" Duct Shroud (Covers Horizontal Ducts) <sup>⑥</sup> .....		3-5	3-5	2-5
BAYCOVR118A	18" Duct Shroud (Covers Horizontal Ducts) <sup>⑥</sup> .....		3-5	3-5	2-5
BAYCURB050A	Flat Roof Full Perimeter Curb (Insulated).....	.74	2-3	3	2-3
BAYCURB051A	Flat Roof Full Perimeter Curb (Insulated).....	.74	3-5	4-5	3½-5
BAYDMPR101A	2-Position Motorized Damper <sup>②⑦⑧⑨⑩</sup> .....		2-3	3	2-3
BAYDMPR102A	2-Position Motorized Damper <sup>②⑦⑧⑨⑩</sup> .....		4-5	4-5	3½-5
BAYECON101A	Economizer with Barometric Relief (Downflow) <sup>①②③④⑩⑪</sup> .....		—	—	2-3
BAYECON102A	Economizer with Barometric Relief (Downflow) <sup>①②③④⑩⑪</sup> .....		—	—	3½-5
BAYECON103A	Economizer with Barometric Relief (Downflow) <sup>①②③④⑩⑪</sup> .....	.50	3	3	—
BAYECON104A	Economizer with Barometric Relief (Downflow) <sup>①②③④⑩⑪</sup> .....	.65	4-5	4-5	—
BAYECON200A	Economizer (Horizontal) <sup>①②③④⑦</sup> .....		—	—	2-3
BAYECON201A	Economizer (Horizontal) <sup>①②③④⑦</sup> .....		—	—	3½-5
BAYECON203A	Economizer (Horizontal) <sup>①②③④⑦</sup> .....	.85	3	3	—
BAYECON204A	Economizer (Horizontal) <sup>①②③④⑦</sup> .....	.85	4-5	4-5	—
BAYENTH001A	Enthalpy Control Kit <sup>③</sup> .....	.2	✓	✓	✓
BAYEXMK001A	Extreme Conditions Mounting Kit.....		✓	✓	✓
BAYEXMK002B	Extreme Conditions Mounting Kit.....		✓	✓	✓
BAYEXMK003A	Extreme Conditions Mounting Kit (Used on Slab Mounts).....		✓	✓	✓
BAYFLTR101C	1-2" Filter Frame <sup>②</sup> -Requires one 20x25 filter (not included).....	.6	3	3	2-3
BAYFLTR201C	1-2" Filter Frame <sup>②</sup> -Requires one 20x20, and one 20x18 filters (not included).....	.6	4-5	4-5	3½-5
BAYLIFT002B	Lifting Lug Kit.....	.5	✓	✓	✓
BAYLOAM105A	Low Ambient Control Kit.....	.5	✓	✓	✓
BAYRLAY004A	Economizer Relay <sup>①</sup> .....		—	—	✓
BAYRLAY006A	Economizer Relay <sup>①</sup> .....	.1	✓	✓	—
BAYOSAC001B	Outside Air Control for V.S. Economizer <sup>③</sup> .....		3,4,5	3,4,5	—
BAYOSAH001A	Manual Fresh Air Damper <sup>②</sup> .....	.6	3	3	2-3
BAYOSAH002A	Manual Fresh Air Damper <sup>②</sup> .....	.8	4-5	4-5	3½-5
BAYQSTK300A	Start Kit.....		—	—	1 Phase Only
BAYSQRD001A	16" Round Duct Adapter <sup>⑤</sup> .....	.5	3	3	2-3
BAYSQRD002A	18" Round Duct Adapter <sup>⑤</sup> .....	.3	4-5	4-5	2-5
BAYUTIL101B	Roof Curb Extension Kit.....		3	3	2-3
BAYUTIL102B	Roof Curb Extension Kit.....		4-5	4-5	3½-5
BAYUV101A	21" Retrofit UVC Lamp Kit.....	.5	3	3	1½-3
BAYUV102A	33" Retrofit UVC Lamp Kit.....	.5	4-5	4-5	3½-5


- ① Relay required with economizer on all heat pump applications.
- ② Must use filter frame when economizer/fresh air kit is used.
- ③ Dry bulb control standard with economizer.
- ④ 2-Stage cooling control required when using economizer.
- ⑤ It is the responsibility of the installing dealer to properly size the ductwork for each specific application.
- ⑥ BAYCOVR112,118A will not cover BAYSQRD002A applications.
- ⑦ Does not contain barometric relief.
- ⑧ Max fresh air - 25%.
- ⑨ For non-continuous fan gas-heating applications, the damper opens only when the OD ambient is above 50° F.
- ⑩ It is the designer/engineer's responsibility to review product specifications prior to equipment selection to insure optimal performance and compliance to codes.
- ⑪ Temperature of mixed air entering the heat exchanger is monitored and fresh air intake may be reduced under certain conditions.
- ⑫ BAYACCDOR1A requires BAYFLTR101B & BAYACCDOR2A requires BAYFLTR201B. They are not backward compatible to BAYFLTR101/201A.
- ⑬ BAYOSAC001B is not compatible with BAYACCDOR1A or BAYACCDOR2A.

EXISTING CURB	NEW UNIT 4WC/DC**A	USE BAYADAP**A
BAYCURB030,38A	024-036	50
BAYCURB030,38A	024-036	52
BAYCURB030,38A	024-036	51
BAYCURB030,38A	024-036	53
BAYCURB030,38A	024-036	54


**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

For complete equipment / combination selections, installation instructions and warranty information, please refer to Product Data/Ratings and/or Installers Guides and Limited Warranty Handbooks.

# Packaged Heat Pump Convertible 2-5 Tons

**4WCY5****Table PK-10-A — 4WCY5 - Gold 15 - Convertible Packaged Heat Pump - R-410A**

Model Number	Capacity	SEER/EER	HSPF	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4WCY5 – 208-230/1/60</b>								
4WCY5024A1000A	25,000	15.00/13.00	8.30	453	18.1	25	69.1	36 x 42 x 49
4WCY5030A1000A	30,000	15.00/12.00	8.20	430	22.8	35	70.0	38 x 42 x 49
4WCY5036A1000A	36,000	15.00/12.00	8.40	439	24.7	40	69.4	38 x 42 x 49
4WCY5042A1000A	41,500	15.00/12.00	8.40	607	28.6	45	72.0	38 x 45 x 59
4WCY5048A1000A	47,500	15.00/12.00	8.40	607	34.2	50	72.0	42 x 45 x 59
4WCY5060A1000A	57,500	15.00/11.50	8.40	623	42.2	60	74.0	42 x 45 x 59

**4WCY4****Table PK-10-B — 4WCY4 - Gold 14 - Convertible Packaged Heat Pump - R-410A**

Model Number	Capacity	SEER/EER	HSPF	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4WCY4 – 208-230/1/60</b>								
4WCY4024A1000B	23,600	14.00/12.00	8.00	453	16.1	25	68	36 x 42 x 49
4WCY4030A1000B	30,000	14.25/12.00	8.00	453	19.2	30	71	36 x 42 x 49
4WCY4036C1000A	37,000	14.00/12.00	8.00	468	24.6	40	69	38 x 42 x 49
4WCY4042B1000A	42,000	14.00/12.00	8.00	607	30.6	45	74	38 x 45 x 59
4WCY4048B1000B	47,500	14.00/12.00	8.00	607	33.9	50	73	38 x 45 x 59
4WCY4060B1000C	58,000	14.00/12.00	8.00	623	39.9	60	76	42 x 45 x 59
<b>4WCY4 – 208-230/3/60</b>								
4WCY4036B3000A	36,000	14.00/11.70	8.00	468	19.8	30	69	38 x 42 x 49
4WCY4048A3000C	47,000	14.00/11.75	8.00	607	26.4	40	73	38 x 45 x 59
4WCY4060A3000C	58,000	14.00/11.50	8.00	623	30.6	45	76	42 x 45 x 59

# Packaged Heat Pump Convertible 2-5 Tons

**Table PK-11-A — Features**

	<b>4WCY5 2-5</b>	<b>4WCY4 2-5</b>
• SEER up to.....	15.00	14.25
• HSPF up to.....	8.20	8.00
• Exclusive <b>Duration™</b> high efficiency compressor with internal overload protection.....	✓	✓
• Factory supplied charge.....	R-410A	R-410A
• Composite <b>Vortica®</b> indoor blower.....	✓	✓
• High efficiency ECM indoor blower motor with <b>Comfort-R™</b> airflow system.....	✓	✓
• All aluminum <b>Spine Fin™</b> outdoor coil.....	✓	✓
• Swept-blade outdoor fan for quiet operation.....	✓	✓
• Architecturally integrated louvers and corner guards.....	✓	✓
• Polyslate gray cabinet.....	✓	✓
• Single stage heating and cooling.....	2 - 3½	✓
• Two stage heating and cooling.....	4, 5	✓
• Start kit - factory installed (single phase only).....	2, 2½	2, 2½
• High pressure cutout.....	✓	✓
• Low pressure cutout.....	✓	✓
• Liquid line drier - factory installed.....	✓	✓
• Non-bleed expansion valves on indoor and outdoor coils.....	✓	✓
• Pressure taps, including liquid line taps, easily accessed and protected inside compressor compartment.....	✓	✓
• Right side electrical service access for high and low voltage connections.....	✓	✓
• Rugged steel basepan features deep drawn duct connections.....	✓	✓
• Steeply sloped composite drainpan.....	✓	✓
• Ships in horizontal configuration and converts quickly for downflow.....	✓	✓
• Copper tube, aluminum fin indoor coil.....	✓	✓
• All models are certified to UL 1995.....	✓	✓
• <b>10-year compressor, 10-year outdoor coil, &amp; 10-year all other functional parts registered limited warranty (Residential Use)①</b> .....	✓	✓
• <b>Extended Warranties Available</b> .....	✓	✓

① Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at [americanstandardair.com](http://americanstandardair.com) or by phone at 800-554-8005; otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on [ASDealerNet.com](http://ASDealerNet.com).

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

# Packaged Heat Pump Convertible 2-5 Tons

**Table PK-12-A — Accessories**

Model Number	Description	Shipping Weight	4WCY5	4WCY4
			2-5	2-5
BAYACCDOR1A	Hinged Filter Access Door®		2-3	2-3
BAYACCDOR2A	Hinged Filter Access Door®		3½-5	3½-5
BAYADAP050A	Adapter Curb (Cabinet A/B)		2-3	2-3
BAYADAP051A	Adapter Curb (Cabinet C)		2-3	2-3
BAYADAP052A	Adapter Curb (Cabinet A/B)		3½-5	3½-5
BAYADAP053A	Adapter Curb (Cabinet C)		3½-5	3½-5
BAYADAP054A	Adapter Curb (Cabinet D)		3½-5	3½-5
BAYASCT001	Anti-Short Cycle Timer③		✓	✓
BAYCCHT101A	Crankcase Heater (230V) (Reciprocating)		2-2½	2-2½
BAYCCHT102A	Crankcase Heater (230V) (Scroll)		3½-5	3½-5
BAYCCHT103A	Crankcase Heater (230V) (Scroll)		3	3
BAYCOVR112A	12" Duct Shroud (Covers Horizontal Ducts)⑥		2-5	2-5
BAYCOVR118A	18" Duct Shroud (Covers Horizontal Ducts)⑥		2-5	2-5
BAYCURB050A	Flat Roof Full Perimeter Curb (Insulated)	.74	2-3	2-3
BAYCURB051A	Flat Roof Full Perimeter Curb (Insulated)	.74	3½-5	3½-5
BAYDMPR101A	2-Position Motorized Damper②⑦⑧⑨⑩		2-3	2-3
BAYDMPR102A	2-Position Motorized Damper②⑦⑧⑨⑩		3½-5	3½-5
BAYECON101A	Economizer with Barometric Relief (Downflow)①②③④⑤⑥		2-3	2-3
BAYECON102A	Economizer with Barometric Relief (Downflow)①②③④⑤⑥		3½-5	3½-5
BAYECON103A	Economizer with Barometric Relief (Downflow)①②③④⑤⑥	.50	—	—
BAYECON104A	Economizer with Barometric Relief (Downflow)①②③④⑤⑥	.65	—	—
BAYECON200A	Economizer (Horizontal)①②③④⑦		2-3	2-3
BAYECON201A	Economizer (Horizontal)①②③④⑦		3½-5	3½-5
BAYENTH001A	Enthalpy Control Kit③	2	✓	✓
BAYEXMK001A	Extreme Conditions Mounting Kit		✓	✓
BAYEXMK002B	Extreme Conditions Mounting Kit		✓	✓
BAYEXMK003A	Extreme Conditions Mounting Kit (Used on Slab Mounts)		✓	✓
BAYFLTR101C	1-2" Filter Frame②-Requires one 20x25 filter (not included)	6	2-3	2-3
BAYFLTR201C	1-2" Filter Frame②-Requires one 20x20, and one 20x18 filters (not included)	6	3½-5	3½-5
BAYLIFT002B	Lifting Lug Kit	5	✓	✓
BAYLOAM105A	Low Ambient Control Kit	5	✓	✓
BAYRLAY004A	Economizer Relay①		✓	✓
BAYOSAH001A	Manual Fresh Air Damper②	6	2-3	2-3
BAYOSAH002A	Manual Fresh Air Damper②	8	3½-5	3½-5
BAYQSTK300A	Start Kit		1 Phase Only	1 Phase Only
BAYSQRD001A	16" Round Duct Adapter⑧	5	2-3	2-3
BAYSQRD002A	18" Round Duct Adapter⑧	3	2-5	2-5
BAYUTIL101B	Roof Curb Extension Kit		2-3	2-3
BAYUTIL102B	Roof Curb Extension Kit		3½-5	3½-5
BAYUV101A	21" Retrofit UVC Lamp Kit	5	2-3	2-3
BAYUV102A	33" Retrofit UVC Lamp Kit	5	3½-5	3½-5


- ① Relay required with economizer on all heat pump applications.
- ② Must use filter frame when economizer/fresh air kit is used.
- ③ Dry bulb control standard with economizer.
- ④ 2-Stage cooling control required when using economizer.
- ⑤ It is the responsibility of the installing dealer to properly size the ductwork for each specific application.
- ⑥ BAYCOVR112,118A will not cover BAYSQRD002A applications.
- ⑦ Does not contain barometric relief.
- ⑧ Max fresh air - 25%.
- ⑨ For non-continuous fan gas-heating applications, the damper opens only when the OD ambient is above 50° F.
- ⑩ It is the designer/engineer's responsibility to review product specifications prior to equipment selection to insure optimal performance and compliance to codes.
- ⑪ Temperature of mixed air entering the heat exchanger is monitored and fresh air intake may be reduced under certain conditions.
- ⑫ BAYACCDOR1A requires BAYFLTR101B & BAYACCDOR2A requires BAYFLTR201B. They are not backward compatible to BAYFLTR101/201A.
- ⑬ BAYOSAC001B is not compatible with BAYACCDOR1A or BAYACCDOR2A.

EXISTING CURB	NEW UNIT 4WCY*A	USE BAYADAP0**A
BAYCURB030,38A	024-036	50
BAYCURB030,38A	024-036	52
BAYCURB030,38A	024-036	51
BAYCURB030,38A	024-036	53
BAYCURB030,38A	024-036	54

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

For complete equipment / combination selections, installation instructions and warranty information, please refer to Product Data/Ratings and/or Installers Guides and Limited Warranty Handbooks.


# Packaged Heat Pump Convertible 2-5 Tons



**4WCC4**

**Table PK-13-A — 4WCC4 - Silver 14 - Convertible Packaged Heat Pump - R-410A**


Model Number	Capacity	SEER/EER	HSPF	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4WCC4 – 208-230/1/60</b>								
4WCC4024A1000A	24,600	14.00/12.00	8.00	402	19.4	30	66	36 x 42 x 49
4WCC4030A1000A	30,400	14.00/12.00	8.00	430	22.6	35	69	38 x 42 x 49
4WCC4036A1000A	35,800	14.00/12.00	8.00	439	24.4	40	69	38 x 42 x 49
4WCC4042A1000A	43,000	14.00/12.00	8.00	548	28.3	45	71	40 x 45 x 59
4WCC4048A1000A	48,000	14.00/12.00	8.00	529	31.9	50	82	40 x 45 x 59
4WCC4060A1000A	58,000	14.00/12.00	8.00	594	39.0	60	77	42 x 45 x 59



**4WCX3  
(3-Phase Only)**

**Table PK-15-B — 4WCX3 - Gold 13 - Convertible Packaged Heat Pump - R-410A**

Model Number	Capacity	SEER/EER	HSPF	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4WCX3 – 208-230/3/60</b>								
4WCX3036A3000B	35,000	13.00/11.00	7.70	468	18.2	30	71	36 x 42 x 49
4WCX3048A3000A	46,000	13.00/10.75	7.70	553	23.6	35	73	38 x 45 x 59
4WCX3060A3000B	58,000	13.00/10.85	7.70	618	31.7	50	72	40 x 45 x 59
<b>4WCX3 – 460/3/60</b>								
4WCX3036A4000B	35,000	13.00/11.00	7.70	468	8.7	15	71	36 x 42 x 49
4WCX3048A4000A	46,000	13.00/10.75	7.70	553	11.7	15	73	38 x 45 x 59
4WCX3060A4000B	58,000	13.00/10.85	7.70	618	19.5	25	72	40 x 45 x 59



**4WCC3  
(3-Phase Only)**

**Table PK-13-C — 4WCC3 - Silver 13 - Convertible Packaged Heat Pump - R-410A**

Model Number	Capacity	SEER/EER	HSPF	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4WCC3 – 208-230/3/60</b>								
4WCC3036A3000B	35,000	13.00/11.00	7.70	468	18.2	30	75	36 x 42 x 49
4WCC3048A3000B	46,000	13.00/10.75	7.70	553	23.6	35	80	38 x 45 x 59
4WCC3060A3000B	58,000	13.00/10.85	7.70	618	31.7	50	79	40 x 45 x 59
<b>4WCC3 – 460/3/60</b>								
4WCC3036A4000B	35,000	13.00/11.00	7.70	468	8.7	15	75	36 x 42 x 49
4WCC3048A4000B	46,000	13.00/10.75	7.70	553	11.7	15	80	38 x 45 x 59
4WCC3060A4000B	58,000	13.00/10.85	7.70	618	19.5	25	79	40 x 45 x 59

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

For complete equipment / combination selections, installation instructions and warranty information, please refer to Product Data/Ratings and/or Installers Guides and Limited Warranty Handbooks.

# Packaged Heat Pump Convertible 2-5 Tons

**Table PK-14-A — Features**

	<b>4WCC4 2-5</b>	<b>4WCX3 3-5</b>	<b>4WCC3 3-5</b>
• SEER up to .....	14.00	13.00	13.00
• HSPF up to .....	8.00	7.70	7.70
• Exclusive <b>Duration™</b> high efficiency compressor with internal overload protection.....	—	✓	—
• Factory supplied charge .....	R-410A	R-410A	R-410A
• Composite <b>Vortica®</b> indoor blower.....	✓	✓	✓
• Direct drive multi-speed indoor blower motors.....	✓	✓	✓
• All aluminum <b>Spine Fin™</b> outdoor coil .....	✓	✓	✓
• Swept-blade outdoor fan for quiet operation .....	—	✓	—
• Architecturally integrated louvers and corner guards.....	—	✓	—
• All steel louvers .....	✓	—	✓
• Polyslate gray cabinet .....	✓	✓	✓
• Single stage cool.....	✓	✓	✓
• High pressure cutout.....	✓	✓	✓
• Low pressure cutout.....	✓	✓	✓
• Liquid line drier - factory installed .....	✓	✓	✓
• Non-bleed expansion valves on indoor and outdoor coils .....	✓	✓	✓
• Pressure taps, including liquid line taps, easily accessed and protected inside compressor compartment ...	✓	✓	✓
• Right side electrical service access for high and low voltage connections.....	✓	✓	✓
• Rugged steel basepan features deep drawn duct connections .....	✓	✓	✓
• Steeply sloped composite drainpan .....	✓	✓	✓
• Ships in horizontal configuration and converts quickly for downflow .....	✓	✓	✓
• Copper tube, aluminum fin indoor coil .....	✓	✓	✓
• All models are certified to UL 1995 .....	✓	✓	✓
• <b>10-year compressor, 10-year outdoor coil, &amp; 10-year all other functional parts registered limited warranty (Residential Use)①</b> .....	✓	✓	✓
• <b>Extended warranties available</b> .....	✓	✓	✓

① Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 800-554-8005; otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ASDealerNet.com.

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

# Packaged Heat Pump Convertible 2-5 Tons

**Table PK-15-A — Accessories**

Model Number	Description	Shipping Weight	4WCC4 2-5	4WCX3 3-5	4WCC3 3-5
BAYACCDOR1A	Hinged Filter Access Door <sup>14</sup>		2-3	3	3
BAYACCDOR2A	Hinged Filter Access Door <sup>14</sup>		3½-5	4-5	4-5
BAYADAP050A	Adapter Curb (Cabinet A/B)		2-3	3	3
BAYADAP051A	Adapter Curb (Cabinet C)		2-3	3	3
BAYADAP052A	Adapter Curb (Cabinet A/B)		3½-5	4-5	4-5
BAYADAP053A	Adapter Curb (Cabinet C)		3½-5	4-5	4-5
BAYADAP054A	Adapter Curb (Cabinet D)		3½-5	4-5	4-5
BAYASCT001	Anti-Short Cycle Timer <sup>5</sup>		✓	✓	✓
BAYCCHT102A	Crankcase Heater (230V) (Scroll)		3½-5	4-5	4-5
BATCCHT103A	Crankcase Heater (230V) (Scroll)		2-3	3	3
BAYCCHT404B	Crankcase Heater (460V) (Scroll)		—	4-5	4-5
BAYCCHT405A	Crankcase Heater (460V) (Scroll)		—	3	3
BAYCOVR112A	12" Duct Shroud (Covers Horizontal Ducts) <sup>8</sup>		2-5	3-5	3-5
BAYCOVR118A	18" Duct Shroud (Covers Horizontal Ducts) <sup>8</sup>		2-5	3-5	3-5
BAYCURB050A	Flat Roof Full Perimeter Curb (Insulated)	74	2-3	3	3
BAYCURB051A	Flat Roof Full Perimeter Curb (Insulated)	74	3½-5	4-5	4-5
BAYDMPR101A	2-Position Motorized Damper <sup>2 9 10 11 12</sup>		2-3	3	3
BAYDMPR102A	2-Position Motorized Damper <sup>2 9 10 11 12</sup>		3½-5	4-5	4-5
BAYECON101A	Economizer with Barometric Relief (Downflow) <sup>1 2 4 5 12 13</sup>		2-3	3	3
BAYECON102A	Economizer with Barometric Relief (Downflow) <sup>1 2 4 5 12 13</sup>		3½-5	4-5	4-5
BAYECON200A	Economizer (Horizontal) <sup>1 2 4 5 9</sup>		2-3	3	3
BAYECON201A	Economizer (Horizontal) <sup>1 2 4 5 9</sup>		3½-5	4-5	4-5
BAYENTH001A	Enthalpy Control Kit <sup>4</sup>	2	✓	✓	✓
BAYEXMK001A	Extreme Conditions Mounting Kit		✓	✓	✓
BAYEXMK002B	Extreme Conditions Mounting Kit		✓	✓	✓
BAYEXMK003A	Extreme Conditions Mounting Kit (Used on Slab Mounts)		✓	✓	✓
BAYFLTR101C	1-2" Filter Frame-Requires one 20x25 filter. (not included) <sup>2</sup>	6	2-3	3	3
BAYFLTR201C	1-2" Filter Frame-Requires one 20x20, & one 20x18 filters. (not inc) <sup>2</sup>	6	3½-5	4-5	4-5
BAYLIFT002B	Lifting Lug Kit	5	✓	✓	✓
BAYLOAM105A	Low Ambient Control Kit	5	✓	✓	✓
BAYLOAM107A	Low Ambient Control Kit	5	✓	—	—
BAYRLAY004A	Economizer Relay <sup>1</sup>		✓	✓	✓
BAYOSAC001B	Outside Air Control for V.S. Economizer <sup>15</sup>		3-5	3-5	3-5
BAYOSAH001A	Manual Fresh Air Damper <sup>2</sup>	6	2-3	3	3
BAYOSAH002A	Manual Fresh Air Damper <sup>2</sup>	8	3½-5	4-5	4-5
BAYQSTK300A	Start Kit		✓	—	—
BAYSQRD001A	16" Round Duct Adapter <sup>7</sup>	5	2-3	3	3
BAYSQRD002A	18" Round Duct Adapter <sup>7</sup>	3	2-5	3-5	3-5
BAYUTIL101B	Roof Curb Extension Kit		2-3	3	3
BAYUTIL102B	Roof Curb Extension Kit		3½-5	4-5	4-5
BAYUV101A	21" Retrofit UVC Lamp Kit	5	2-3	3	3
BAYUV102A	33" Retrofit UVC Lamp Kit	5	3½-5	4-5	4-5

- ① Relay required with economizer on all heat pump applications.
- ② Must use filter frame when economizer/fresh air kit is used.
- ③ Ships knocked down.
- ④ Dry bulb control standard with economizer.
- ⑤ 2-Stage cooling control required when using economizer.
- ⑥ Do not use with electronic thermostats.
- ⑦ It is the responsibility of the installing dealer to properly size the ductwork for each specific application.
- ⑧ BAYCOVR112,118A will not cover BAYSQRD002A applications.
- ⑨ Does not contain barometric relief.
- ⑩ Max fresh air - 25%.
- ⑪ For non-continuous fan gas-heating applications, the damper opens only when the OD ambient is above 50° F.
- ⑫ It is the designer/engineer's responsibility to review product specifications prior to equipment selection to insure optimal performance and compliance to codes.
- ⑬ Temperature of mixed air entering the heat exchanger is monitored and fresh air intake may be reduced under certain conditions.
- ⑭ BAYACCDOR1A requires BAYFLTR101B & BAYACCDOR2A requires BAYFLTR201B. They are not backward compatible to BAYFLTR101/201A.
- ⑮ BAYOSAC001B is not compatible with BAYACCDOR1A or BAYACCDOR2A.


\*\* Single-phase units phasing out. No longer manufactured after 12-31-14.

EXISTING CURB	NEW UNIT 4WC**A	USE BAYADAP**A
BAYCURB030,38A	024-036	50
BAYCURB030,38A	042-060	52
BAYCURB033A	024-036	51
BAYCURB033A	024-060	53
BAYCURB034A	042-060	54

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

For complete equipment / combination selections, installation instructions and warranty information, please refer to Product Data/Ratings and/or Installers Guides and Limited Warranty Handbooks.

# Packaged Heat Pump Over/Under 2-5 Tons


**4WHC4**

- **Duration®** compressor
- Over (supply) under (return) air
- Compressor internal overload protection
- Solenoid operated switchover valve
- Demand defrost control system
- Multi-speed direct drive blower motor
- High efficiency multi-speed ECM indoor motor on 4WHC4024-4036. 4WHC4042 models are variable speed.
- Weather resistant Powder Paint
- Copper tube, aluminum plate fin coils
- Top discharge condensing fan
- Factory installed wrap-around coil guard
- Top access to supplementary heater
- Pressure taps for refrigerant checks
- Polarized plug for easy field connection of low voltage to supplementary heaters
- Low ambient cooling to 55°F as manufactured
- Low ambient cooling to 0°F with accessory BAYLOAM011A
- All models are certified to UL 1995
- **10-year registered limited warranty on compressor, outdoor coil and all other functional parts (Residential Use)**
- **Optional extended warranties**

**Table PK-16-A — Silver 14 – Over/Under Horizontal Unit – R-410A**

Model No.	Dimensions		Shipping						
	Capacity	SEER/EER	HSPF	(in.) H x D x W		Weight (lbs.)	MCA*	Max Fuse*	Sound Rating
4WHC4024A1000A	24,800	16/13.6	8.2	31 x 44 x 32		322	18.7	25	74
4WHC4030A1000A	30,000	14/12	8	31 x 44 x 32		322	21.1	30	74
4WHC4036A1000A	35,800	14/12	8	31 x 44 x 32		322	26.2	40	75
4WHC4042A1000A	39,500	14/12	8	31 x 44 x 32		353	30.5	45	75
<b>Tons</b>	<b>Supply H x W</b>	<b>Return H x W</b>							
2 – 3½	8¾ x 27¾	16¾ x 27¾							

Dimensions are in inches. See Outline Dimensions.

\* Information subject to change. Please confirm with current Product Data/Service Facts for current factory production.

Compressor Types are: R1 = Reciprocating One Cylinder, R2 = Reciprocating Two Cylinder, S = Scroll

**Table PK-16-B— Supplementary Heaters – Heater Matrix**

Model No.①	Power Supply	kW Ratings	Used With	Shipping Weight
BAYHTRC106A	208/240/1/60	4.33/5.76 kW	4WHC4024-042	9
BAYHTRC109A	208/240/1/60	6.12/8.16 kW	4WHC4036-4042	10
BAYHTRC110A	208/240/1/60	7.93/10.56 kW	4WHC4030	10
BAYHTRC111A	208/240/1/60	7.98/10.56 kW	4WHC4024, 4036 & 4042	10
BAYHTRC117A	208/240/1/60	12.98/17.28 kW	4WHC4030-4042	23

**Table PH-16-C — Accessories/Comfort Controls**

Model No.	Description	Used With	Shipping Weight
BAYASCT001②③	Anti-Short Cycle Timer	All 4WHC4 Models	1
BAYECMT003A	Extreme Conditions Mounting Kit (Slab or Rack Mount)	All 4WHC4 Models	
BAYLOAM011A	Low Ambient Cooling Kit	All 4WHC4 Models	5
TAYASCT501A③	5 Minute Delay Relay	All 4WHC4 Models	2
TCONT402A	3Heat/2Clg (Heat Pump/A/C)	All 4WHC4 Models	1
TCONT602A	2Heat/2Clg (Heat Pump/A/C)	All 4WHC4 Models	1
TCONT802A	3Heat/2Clg (Heat Pump/A/C)	All 4WHC4 Models	1
TCONT803A	3Heat/2Clg (Heat Pump/A/C) w/Humidity Display	All 4WHC4 Models	1

① Heaters must have an "A" in eleventh digit to work on 4WHC4 models.

② Not for use with electronic thermostats.


③ Activated on Power Off.

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

For complete equipment / combination selections, installation instructions and warranty information, please refer to Product Data/Ratings and/or Installers Guides and Limited Warranty Handbooks.




# Packaged Gas/Electric Convertible 2-5 Tons



**4YCZ6**

**Table PK-17-A — 4YCZ6 - Platinum 16 - Convertible Packaged Gas/Electric - R-410A**

Model Number	Cooling Capacity (BTUH)	Heating Capacity Output (1 Stg./2 Stg.)	SEER	EER High/Low	AFUE(%)	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dim. (in.) H x D x W
<b>4YCZ6 – 208-230/1/60</b>										
4YCZ6036C1070A	35,600	45,000/57,000	16.60	12.00/13.60	81.0	488	26.0	40	70	38 x 42 x 49
4YCZ6036C1090A	35,600	58,000/73,000	16.60	12.00/13.60	81.0	488	26.0	40	70	38 x 42 x 49
4YCZ6048C1090A	48,000	58,000/73,000	16.00	12.00/13.48	81.0	659	34.1	50	71	42 x 45 x 59
4YCZ6048C1115A	48,000	75,000/93,000	16.00	12.00/13.48	81.0	665	34.1	50	71	42 x 45 x 59
4YCZ6060C1115A	57,500	75,000/93,000	15.10	11.40/12.64	81.0	676	44.4	60	73	42 x 45 x 59
<b>4YCZ6 – 208-230/3/60</b>										
4YCZ6036A3075B	35,600	45,000/60,000	16.60	12.00/13.60	80.0	488	19.1	30	70	38 x 42 x 49
4YCZ6036A3096B	35,600	57,600/77,000	16.60	12.00/13.60	80.0	493	19.1	30	70	38 x 42 x 49
4YCZ6048A3096B	48,000	57,600/77,000	16.00	12.00/13.48	80.0	659	25.2	35	71	42 x 45 x 59
4YCZ6048A3120B	48,000	72,000/96,000	16.00	12.00/13.48	80.0	665	25.2	35	71	42 x 45 x 59
4YCZ6060A3120B	57,500	72,000/96,000	15.10	11.40/12.65	80.0	676	28.6	40	73	42 x 45 x 59
<b>4YCZ6 – 460/3/60</b>										
4YCZ6036A4075C	35,600	45,000/60,000	16.60	12.00/13.60	79.0	488	10.4	15	70	38 x 42 x 49
4YCZ6036A4096C	35,600	57,600/77,000	16.60	12.00/13.60	80.0	493	10.4	15	70	38 x 42 x 49
4YCZ6048A4096C	48,000	57,600/77,000	16.00	12.00/13.48	80.0	659	15.3	20	71	42 x 45 x 59
4YCZ6048A4120C	48,000	72,000/96,000	16.00	12.00/13.48	80.0	665	15.3	20	71	42 x 45 x 59
4YCZ6060A4120C	57,500	72,000/96,000	15.10	11.40/12.65	80.0	676	17.2	20	73	42 x 45 x 59



**4ICY4**


**Table PK-17-B — 4ICY4 - Gold 14 - Convertible Packaged Gas/Electric - R-410A**

Model Number	Cooling Capacity (BTUH)	Heating Capacity Output (1 Stg./2 Stg.)	SEER/EER	AFUE(%)	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4ICY4 – 208-230/1/60</b>									
4ICY4024C1060A	23,400	39,000/49,000	14.00/12.00	81.0	481	16.5	25	68	36 x 42 x 49
4ICY4030C1070A	30,000	45,000/57,000	14.00/12.00	81.0	481	19.2	30	71	36 x 42 x 49
4ICY4036C1070A	38,000	45,000/57,000	14.20/12.00	81.0	488	24.6	40	69	38 x 42 x 49
4ICY4036C1090A	38,000	58,000/73,000	14.20/12.00	81.0	488	24.6	40	69	38 x 42 x 49
4ICY4042C1090A	42,000	58,000/73,000	14.25/12.00	81.0	653	31.5	50	74	42 x 45 x 59
4ICY4048C1090A	48,500	58,000/73,000	14.20/12.00	81.0	669	35.4	50	73	42 x 45 x 59
4ICY4048C1115A	48,500	75,000/93,000	14.20/12.00	81.0	675	35.4	50	73	42 x 45 x 59
4ICY4060C1115A	58,500	75,000/93,000	14.00/12.00	81.0	676	43.3	60	76	42 x 45 x 59
<b>4ICY4 – 208-230/3/60</b>									
4ICY4036B3075A	38,000	45,000/60,000	14.20/12.00	80.0	488	19.8	30	69	38 x 42 x 49
4ICY4036B3096A	38,000	57,600/77,000	14.20/12.00	80.0	493	19.8	30	69	38 x 42 x 49
4ICY4048B3096A	48,000	57,600/77,000	14.20/11.90	80.0	653	26.4	40	73	38 x 45 x 59
4ICY4048B3120A	48,000	72,000/96,000	14.20/11.90	80.0	659	26.4	40	73	38 x 45 x 59
4ICY4060A3120B	58,500	72,000/96,000	14.00/12.00	80.0	676	30.6	45	76	42 x 45 x 59

For dimensional/outline drawings, please refer to Product Data.

For information on Roof Curbs, please refer to the Accessories/Information Tab.

# Packaged Gas/Electric Convertible 2-5 Tons



**4YCY5**

**Table PK-18-A — 4YCY5- Gold 15 - Convertible Packaged Gas/Electric - R-410A**

Model Number	Cooling Capacity (BTUH)	Heating Capacity Output (1 Stg./2 Stg.)	SEER/EER	AFUE(%)	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4YCY5- 208-230/1/60</b>									
4YCY5024A1060A	-	-	15.00/12.20	-	-	-	-	-	36 x 42 x 49
4YCY5030A1070A	-	-	15.00/12.20	-	-	-	-	-	36 x 42 x 49
4YCY5036A1070A	-	-	15.20/12.20	-	-	-	-	-	38 x 42 x 49
4YCY5036A1090A	-	-	15.20/12.20	-	-	-	-	-	38 x 42 x 49
4YCY5042A1090A	-	-	15.25/12.20	-	-	-	-	-	38 x 45 x 59
4YCY5048A1090A	-	-	15.20/12.20	-	-	-	-	-	38 x 45 x 59
4YCY5048A1115A	-	-	15.20/12.20	-	-	-	-	-	38 x 45 x 59
4YCY5060A1115A	-	-	15.00/11.40	-	-	-	-	-	42 x 45 x 59

**Table PK-18-B — Features**

	<b>4YCY5 2-5</b>	<b>4YCY4 2-5</b>	<b>4YCY3 2-5</b>
• SEER up to.....	16.60	14.25	15.00
• Exclusive <b>Duration™</b> high efficiency compressor with internal overload protection.....	✓	✓	✓
• Factory supplied charge.....	R-410A	R-410A	R-410A
• Composite <b>Vortica®</b> indoor blower.....	✓	✓	✓
• High efficiency ECM indoor blower motor with <b>Comfort-R™</b> airflow system.....	✓	✓	✓
• All aluminum <b>Spine Fin™</b> outdoor coil.....	✓	✓	✓
• Swept-blade outdoor fan for quiet operation .....	✓	✓	✓
• Architecturally integrated louvers and corner guards.....	✓	✓	✓
• Polyslate gray cabinet.....	✓	✓	✓
• Stainless steel heat exchanger and burners .....	✓	✓	✓
• Single stage cool.....	—	✓	2-3½
• 2-stage cooling.....	✓	—	4,5
• 2-stage gas.....	✓	✓	✓
• Start kit - factory installed (single phase only).....	—	2, 2½	—
• High pressure cutout.....	✓	✓	✓
• Low pressure cutout.....	✓	✓	✓
• Liquid line drier - factory installed.....	✓	✓	✓
• Non-bleed expansion valves on indoor coil.....	✓	✓	✓
• Pressure taps, including liquid line taps, easily accessed and protected inside compressor compartment.....	✓	✓	✓
• Right side electrical service access for high and low voltage connections.....	✓	✓	✓
• Rugged steel basepan features deep drawn duct connections.....	✓	✓	✓
• Steeply sloped composite drainpan.....	✓	✓	✓
• Ships in horizontal configuration and converts quickly for downflow.....	✓	✓	✓
• Copper tube, aluminum fin indoor coil.....	✓	✓	3,4,5
• All aluminum indoor coil.....	—	—	2, 2½, 3½
• All models are certified to ANSI 221.47/CSA 2.3.....	✓	✓	✓
• <b>20-year heat exchanger, 12-year compressor, 10-year outdoor coil, &amp; 10-year all other functional parts registered limited warranty (Residential Use)①</b> .....	✓	—	—
• <b>20-year heat exchanger, 10-year compressor, 10-year outdoor coil, &amp; 10-year all other functional parts registered limited warranty (Residential Use)①</b> .....	—	✓	✓
• <b>Extended warranties available</b> .....	✓	✓	✓

① Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 800-554-8005; otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ASDealerNet.com.

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

# Packaged Gas/Electric Convertible 2-5 Tons

**Table PK-19-A — Accessories**

Model Number	Description	Shipping Weight	4YCZ6 3-5	4YCY4 2-5	4YCY5 2-5
BAYACCDOR1A	Hinged Filter Access Door <sup>②</sup>		3	2-3	2-3
BAYACCDOR2A	Hinged Filter Access Door <sup>②</sup>		3½-5	3½-5	3½-5
BAYADAP050A	Adapter Curb (Cabinet A/B)		3	2-3	2-3
BAYADAP051A	Adapter Curb (Cabinet C)		3	2-3	2-3
BAYADAP052A	Adapter Curb (Cabinet A/B)		4-5	3½-5	3½-5
BAYADAP053A	Adapter Curb (Cabinet C)		4-5	3½-5	3½-5
BAYADAP054A	Adapter Curb (Cabinet D)		4-5	3½-5	3½-5
BAYASCT001	Anti-Short Cycle Timer <sup>④</sup>		✓	✓	—
BAYCCHT101A	Crankcase Heater (230v) (Reciprocating)		—	2-2½	2-2½
BAYCCHT102A	Crankcase Heater (230v) (Scroll)		4-5	3½-5	3½-5
BAYCCHT103A	Crankcase Heater (230V) (Scroll)		3	3	2-3
BAYCCHT404B	Crankcase Heater (460v) (Scroll)		4-5	—	—
BAYCCHT405A	Crankcase Heater (460v) (Scroll)		3	—	—
BAYCOVR112A	12" Duct Shroud (Covers Horizontal Ducts) <sup>⑤</sup>		3-5	2-5	2-5
BAYCOVR118A	18" Duct Shroud (Covers Horizontal Ducts) <sup>⑤</sup>		3-5	2-5	2-5
BAYCURB050A	Flat Roof Full Perimeter Curb (Insulated)	.74	3	2-3	2-3
BAYCURB051A	Flat Roof Full Perimeter Curb (Insulated)	.74	4-5	3½-5	3½-5
BAYDMPR101A	Motorized Fresh Air Damper <sup>①⑦⑧⑨⑩</sup>		3	2-3	2-3
BAYDMPR102A	Motorized Fresh Air Damper <sup>①⑦⑧⑨⑩</sup>		4-5	3½-5	3½-5
BAYECON101A	Economizer with Barometric Relief (Downflow) <sup>①②③④⑩</sup>	.50	—	2-3	2-3
BAYECON102A	Economizer with Barometric Relief (Downflow) <sup>①②③④⑩</sup>	.65	—	3½-5	3½
BAYECON103A	Economizer with Barometric Relief (Downflow) <sup>①②③④⑩</sup>		3	—	—
BAYECON104A	Economizer with Barometric Relief (Downflow) <sup>①②③④⑩</sup>		4-5	—	4-5
BAYECON200A	Economizer (Horizontal) <sup>①②③⑦</sup>	.85	—	2-3	2-3
BAYECON201A	Economizer (Horizontal) <sup>①②③⑦</sup>	.85	—	3½-5	3½
BAYECON203A	Economizer (Horizontal) <sup>①②③⑦</sup>		3	—	—
BAYECON204A	Economizer (Horizontal) <sup>①②③⑦</sup>		4-5	—	4-5
BAYENTH001A	Enthalpy Control Kit <sup>②</sup>	.2	✓	✓	✓
BAYEXMK001A	Extreme Conditions Mounting Kit (Used on BAYCURB & BAYADAP)		✓	✓	✓
BAYEXMK002B	Extreme Conditions Mounting Kit (Used on BAYUTIL)		✓	✓	✓
BAYEXMK003A	Extreme Conditions Mounting Kit (Used on Slab Mounts)		✓	✓	✓
BAYFLTR101C	1-2" Filter Frame <sup>①</sup> -Requires one 20x25 filter (not included)	.6	3	2-3	2-3
BAYFLTR201C	1-2" Filter Frame <sup>①</sup> -Requires one 20x20, and one 20x18 filters (not included)	.6	4-5	3½-5	3½-5
BAYLIFT002B	Lifting Lug Kit	.5	✓	✓	✓
BAYLOAM105A	Low Ambient Control Kit	.5	✓	✓	✓
BAYLPKT100A	LP Conversion Kit		115k	115k	115k
BAYLPKT101A	LP Conversion Kit		60k, 90k	60K, 90K	60K, 90K
BAYLPKT102A	LP Conversion Kit		70k	70K	70K
BAYOSAC001B	Outside Air Control for V.S. Economizer <sup>⑨</sup>		3,4,5	—	4-5
BAYOSAH001A	Manual Fresh Air Damper <sup>①</sup>	.6	3	2-3	2-3
BAYOSAH002A	Manual Fresh Air Damper <sup>①</sup>	.8	4-5	3½-5	3½-5
BAYQSTK301A	Start Kit		—	✓	✓
BAYSQRD001A	16" Round Duct Adapter <sup>⑤</sup>	.5	3	2-3	2-3
BAYSQRD002A	18" Round Duct Adapter <sup>⑤</sup>	.3	4-5	2-5	2-5
BAYUTIL101B	Roof Curb Utility Extension Kit		3	2-3	2-3
BAYUTIL102B	Roof Curb Utility Extension Kit		4-5	3½-5	3½-5
BAYUV101A	21" Retrofit UVC Lamp Kit	.5	2-3	2-3	2-3
BAYUV102A	33" Retrofit UVC Lamp Kit	.5	3½-5	3½-5	3½-5


- ① Must use filter frame when economizer/fresh air kit is used.
- ② Dry bulb control standard with economizer.
- ③ 2-Stage cooling control required when using economizer.
- ④ Do not use with electronic thermostats.
- ⑤ It is the responsibility of the installing dealer to properly size the ductwork for each specific application.
- ⑥ BAYCOVR112,118A will not cover BAYSQRD002A applications.
- ⑦ Does not contain barometric relief.
- ⑧ Max fresh air - 25%.
- ⑨ For non-continuous fan gas-heating applications, the damper opens only when the OD ambient is above 50° F.
- ⑩ It is the designer/engineer's responsibility to review product specifications prior to equipment selection to insure optimal performance and compliance to codes.
- ⑪ Temperature of mixed air entering the heat exchanger is monitored and fresh air intake may be reduced under certain conditions.
- ⑫ BAYACCDOR1A requires BAYFLTR101B & BAYACCDOR2A requires BAYFLTR201B. They are not backward compatible to BAYFLTR101/201A.
- ⑬ BAYOSAC001B is not compatible with BAYACCDOR1A or BAYACCDOR2A

EXISTING CURB	NEW UNIT 4TC/WC/YC****A	USE BAYADAP0**A
BAYCURB030,38A	024-036	50
BAYCURB030,38A	042-060	52
BAYCURB033A	024-036	51
BAYCURB033A	042-060	53
BAYCURB034A	042-060	54

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

For complete equipment / combination selections, installation instructions and warranty information, please refer to Product Data/Ratings and/or Installers Guides and Limited Warranty Handbooks.

# Packaged Gas/Electric Convertible 3-5 Tons



**4YCX3  
(3-Phase Only)**

**Table PK-20-A — 4YCX3 - Gold 13 - Convertible Packaged Gas/Electric - R-410A**

Model Number	Cooling Capacity (BTUH)	Heating Capacity Input/Output	SEER/EER	AFUE(%)	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4YCX3 – 208-230/3/60</b>									
4YCX3036A3064B	36,000	64,000/51,000	13.00/11.00	80.0	493	17.2	25	71	38 x 42 x 49
4YCX3036A3075B	36,000	75,000/60,000	13.00/11.00	80.0	488	17.2	25	71	38 x 42 x 49
4YCX3036A3096B	36,000	96,000/76,000	13.00/11.00	80.0	493	17.2	25	71	38 x 42 x 49
4YCX3048A3075B	46,500	75,000/61,000	13.00/11.00	80.0	645	24.0	35	73	38 x 45 x 59
4YCX3048A3096B	46,500	96,000/77,000	13.00/11.00	80.0	653	24.0	35	73	38 x 45 x 59
4YCX3048A3120B	46,500	120,000/95,000	13.00/11.00	80.0	659	24.0	35	73	38 x 45 x 59
4YCX3060A3096B	60,000	96,000/77,000	13.00/10.95	80.0	678	31.7	50	75	42 x 45 x 59
4YCX3060A3120B	60,000	120,000/95,000	13.00/10.95	80.0	684	28.6	40	75	42 x 45 x 59
<b>4YCX3 – 460/3/60</b>									
4YCX3036A4064B	36,000	64,000/51,000	13.00/11.00	80.0	448	9.5	15	71	38 x 42 x 49
4YCX3036A4075B	36,000	75,000/60,000	13.00/11.00	80.0	448	9.5	15	71	38 x 42 x 49
4YCX3036A4096B	36,000	96,000/76,000	13.00/11.00	80.0	493	9.5	15	71	38 x 42 x 49
4YCX3048A4075B	46,500	75,000/61,000	13.00/11.00	80.0	645	11.7	15	73	38 x 45 x 59
4YCX3048A4096B	46,500	96,000/77,000	13.00/11.00	80.0	653	11.7	15	73	38 x 45 x 59
4YCX3048A4120B	46,500	120,000/95,000	13.00/11.00	80.0	659	11.7	15	73	38 x 45 x 59
4YCX3060A4096A	60,000	96,000/77,000	13.00/10.95	80.0	678	19.5	25	75	42 x 45 x 59
4YCX3060A4120B	60,000	120,000/95,000	13.00/10.95	80.0	684	19.5	25	75	42 x 45 x 59

**For dimensional/outline drawings, please refer to Product Data.**


**For information on Roof Curbs, please refer to the Accessories/Information Tab.**

For complete equipment / combination selections, installation instructions and warranty information, please refer to Product Data/Ratings and/or Installers Guides and Limited Warranty Handbooks.

# Packaged Gas/Electric Convertible 2-5 Tons

**Table PK-21-A — 4YCC4 - Silver 14 - Convertible Packaged Gas/Electric - R-410A**


Model Number	Cooling Capacity (BTUH)	Heating Capacity Input/Output	SEER/EER	AFUE(%)	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4YCC4 – 208-230/1/60</b>									
4YCC4024A1060A	24,600	60,000/49,000	14.00/12.00	81.0	481	19.1	30	67	36 x 42 x 49
4YCC4030A1070A	28,200	70,000/57,000	14.00/12.00	81.0	481	22.6	35	69	36 x 42 x 49
4YCC4036A1070A	37,000	70,000/57,000	14.00/12.00	81.0	488	24.5	40	69	38 x 42 x 49
4YCC4036A1090A	37,000	90,000/73,000	14.00/12.00	81.0	493	24.5	40	69	38 x 42 x 49
4YCC4042A1060A	40,500	60,000/49,000	14.00/12.00	81.0	653	28.5	45	75	36 x 45 x 59
4YCC4042A1090A	40,500	90,000/73,000	14.00/12.00	81.0	653	28.5	45	75	36 x 45 x 59
4YCC4048A1070A	46,500	70,000/57,000	14.00/11.50	81.0	645	32.0	50	73	40 x 45 x 59
4YCC4048A1090A	46,500	90,000/73,000	14.00/11.50	81.0	653	32.0	50	73	40 x 45 x 59
4YCC4060A1090A	58,000	90,000/73,000	14.00/11.50	81.0	678	39.1	60	73	40 x 45 x 59
4YCC4060A1115A	58,000	115,000/93,000	14.00/11.50	81.0	684	39.1	60	73	40 x 45 x 59



**4YCC4**

**Table PK-21-B — 4YCC3 - Silver 13 - Convertible Packaged Gas/Electric - R-410A**

Model Number	Cooling Capacity (BTUH)	Heating Capacity Input/Output	SEER/EER	AFUE(%)	Shipping Weight	MCA	Max Fuse	Sound Rating	Cabinet Dimensions (in.) H x D x W
<b>4YCC3 – 208-230/3/60</b>									
4YCC3036A3064B	35,000	64,000/51,000	13.00/11.00	80.0	488	17.2	25	75	36 x 42 x 49
4YCC3036A3075B	35,000	75,000/60,000	13.00/11.00	80.0	488	17.2	25	75	36 x 42 x 49
4YCC3036A3096B	35,000	96,000/76,000	13.00/11.00	80.0	493	17.2	25	75	36 x 42 x 49
4YCC3048A3075B	46,500	75,000/61,000	13.00/11.00	80.0	645	24.0	35	80	38 x 45 x 59
4YCC3048A3096B	46,500	96,000/77,000	13.00/11.00	80.0	653	24.0	35	80	38 x 45 x 59
4YCC3048A3120B	46,500	120,000/95,000	13.00/11.00	80.0	659	24.0	35	80	38 x 45 x 59
4YCC3060A3096B	58,000	96,000/77,000	13.00/10.95	80.0	678	31.5	50	79	40 x 45 x 59
4YCC3060A3120B	58,000	120,000/95,000	13.00/10.95	80.0	684	28.6	40	79	40 x 45 x 59
<b>4YCC3 – 460/3/60</b>									
4YCC3036A4064B	35,000	64,000/51,000	13.00/11.00	80.0	488	9.5	15	75	36 x 42 x 49
4YCC3036A4075B	35,000	75,000/60,000	13.00/11.00	80.0	488	9.5	15	75	36 x 42 x 49
4YCC3036A4096B	35,000	96,000/76,000	13.00/11.00	80.0	493	9.5	15	75	36 x 42 x 49
4YCC3048A4075B	46,500	75,000/61,000	13.00/11.00	80.0	645	11.7	15	80	38 x 45 x 59
4YCC3048A4096B	46,500	96,000/77,000	13.00/11.00	80.0	653	11.7	15	80	38 x 45 x 59
4YCC3048A4120B	46,500	120,000/95,000	13.00/11.00	80.0	659	11.7	15	80	38 x 45 x 59
4YCC3060A4096B	58,000	96,000/77,000	13.00/10.95	80.0	678	19.3	25	79	40 x 45 x 59
4YCC3060A4120B	58,000	120,000/95,000	13.00/10.95	80.0	684	19.3	25	79	40 x 45 x 59



**4YCC3  
(3-Phase Only)**

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

For complete equipment / combination selections, installation instructions and warranty information, please refer to Product Data/Ratings and/or Installers Guides and Limited Warranty Handbooks.

# Packaged Gas/Electric Convertible 2-5 Tons

**Table PK-22-A — Features**

	4YCC4 2-5	4YCX3 3-5	4YCC3 3-5
• SEER up to.....	14.00	13.00	13.00
• Exclusive <b>Duration™</b> high efficiency compressor with internal overload protection.....	✓	✓	✓
• Factory supplied charge.....	R-410A	R-410A	R-410A
• Composite <b>Vortica®</b> indoor blower.....	✓	✓	✓
• Direct drive multi-speed indoor blower motors.....	✓	✓	✓
• All aluminum <b>Spine Fin™</b> outdoor coil.....	✓	✓	✓
• Swept-blade outdoor fan for quiet operation.....	✓	✓	—
• Architecturally integrated louvers and corner guards.....	—	✓	—
• All steel louvers.....	✓	—	✓
• Polyslate gray cabinet.....	✓	✓	✓
• Stainless steel heat exchanger and burners.....	✓	✓	✓
• Single stage cool.....	✓	✓	✓
• Single stage gas.....	✓	✓	✓
• Start kit - factory installed (single phase only).....	✓	—	—
• High pressure cutout.....	✓	✓	✓
• Low pressure cutout.....	✓	✓	✓
• Liquid line drier - factory installed.....	✓	✓	✓
• Non-bleed expansion valves on indoor coil.....	✓	✓	✓
• Pressure taps, including liquid line taps, easily accessed and protected inside compressor compartment.....	✓	✓	✓
• Right side electrical service access for high and low voltage connections.....	✓	✓	✓
• Rugged steel basepan features deep drawn duct connections.....	✓	✓	✓
• Steeply sloped composite drainpan.....	✓	✓	✓
• Ships in horizontal configuration and converts quickly for downflow.....	✓	✓	✓
• Copper tube, aluminum fin indoor coil.....	5	✓	✓
• All Aluminum indoor coil.....	2 - 4	—	—
• All models are certified to ANSI 221.47/CSA 2.3.....	✓	✓	✓
• <b>20-year heat exchanger, 10-year compressor, 10-year outdoor coil, &amp; 10-year all other functional parts registered limited warranty (Residential Use)①</b> .....	✓	✓	—
• <b>10-year heat exchanger, 10-year compressor, 10-year outdoor coil, &amp; 10-year on all other functional parts registered limited warranty (Residential Use)①</b> ....	—	—	✓
• <b>Extended warranties available</b> .....	✓	✓	✓

① Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 800-554-8005; otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ASDealerNet.com.

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

# Packaged Gas/Electric Convertible 2-5 Tons

**Table PK-23-A — Accessories**

Model Number	Description	Shipping Weight	4YCC4 2-5	4YCX3 3-5	4YCC3 3-5
BAYACCDOR1A	Hinged Filter Access Door <sup>⑫</sup>		2-3	3-3	3-3
BAYACCDOR2A	Hinged Filter Access Door <sup>⑫</sup>		3½-5	4-5	4-5
BAYADAP050A	Adapter Curb (Cabinet A/B)		2-3	3	3
BAYADAP051A	Adapter Curb (Cabinet C)		2-3	3	3
BAYADAP052A	Adapter Curb (Cabinet A/B)		3½-5	4-5	4-5
BAYADAP053A	Adapter Curb (Cabinet C)		3½-5	4-5	4-5
BAYADAP054A	Adapter Curb (Cabinet D)		3½-5	4-5	4-5
BAYASCT001	Anti-Short Cycle Timer <sup>④</sup>		✓	✓	✓
BAYCCHT102A	Crankcase Heater (230v) (Scroll)		3½-5	4-5	4-5
BAYCCHT103A	Crankcase Heater (230v) (Scroll)		2-3	3	3
BAYCCHT404B	Crankcase Heater (460v) (Scroll)		—	4-5	4-5
BAYCCHT405A	Crankcase Heater (460v) (Scroll)		—	3	3
BAYCOVR112A	12" Duct Shroud (Covers Horizontal Ducts) <sup>⑥</sup>		2-5	3-5	3-5
BAYCOVR118A	18" Duct Shroud (Covers Horizontal Ducts) <sup>⑥</sup>		2-5	3-5	3-5
BAYCURB050A	Flat Roof Full Perimeter Curb (Insulated)	74	2-3	3	3
BAYCURB051A	Flat Roof Full Perimeter Curb (Insulated)	74	3½-5	4-5	4-5
BAYDMPR101A	Motorized Fresh Air Damper <sup>①⑦⑧⑨⑩</sup>		2-3	3	3
BAYDMPR102A	Motorized Fresh Air Damper <sup>①⑦⑧⑨⑩</sup>		3½-5	4-5	4-5
BAYECON101A	Economizer with Barometric Relief (Downflow) <sup>①②③⑩⑪</sup>	50	2-3	3	3
BAYECON102A	Economizer with Barometric Relief (Downflow) <sup>①②③⑩⑪</sup>	65	3½-5	4-5	4-5
BAYECON200A	Economizer (Horizontal) <sup>①②③⑦</sup>	85	2-3	3	3
BAYECON201A	Economizer (Horizontal) <sup>①②③⑦</sup>	85	3½-5	4-5	4-5
BAYENTH001A	Enthalpy Control Kit <sup>②</sup>	2	✓	✓	✓
BAYEXMK001A	Extreme Conditions Mounting Kit (Used on BAYCURB & BAYADAP)		✓	✓	✓
BAYEXMK002B	Extreme Conditions Mounting Kit (Used on BAYUTIL)		✓	✓	✓
BAYEXMK003A	Extreme Conditions Mounting Kit (Used on Slab Mounts)		✓	✓	✓
BAYFLTR101C	1-2" Filter Frame <sup>①</sup> -Requires one 20x25 filter (not included)	6	2-3	3	3
BAYFLTR201C	1-2" Filter Frame <sup>①</sup> -Requires one 20x20, & one 20x18 filters (not incl)	6	3½-5	4-5	4-5
BAYLIFT002B	Lifting Lug Kit	5	✓	✓	✓
BAYLOAM105A	Low Ambient Control Kit	5	✓	✓	✓
BAYLOAM107A	Low Ambient Control Kit	5	✓	—	—
BAYLPKT100A	LP Conversion Kit		115k	115k	115k
BAYLPKT101A	LP Conversion Kit		60K, 90K	60K, 90K	60K, 90K
BAYLPKT102A	LP Conversion Kit		70K	70K	70K
BAYOSAH001A	Manual Fresh Air Damper <sup>①</sup>	6	2-3	3	3
BAYOSAH002A	Manual Fresh Air Damper <sup>①</sup>	8	3½-5	4-5	4-5
BAYQSTK301A	Start Kit		✓	✓	✓
BAYSQRD001A	16" Round Duct Adapter <sup>⑤</sup>	5	2-3	3	3
BAYSQRD002A	18" Round Duct Adapter <sup>⑤</sup>	3	2-5	3-5	3-5
BAYUTIL101B	Roof Curb Utility Extension Kit		2-3	3	3
BAYUTIL102B	Roof Curb Utility Extension Kit		3½-5	4-5	4-5
BAYUV101A	21" Retrofit UVC Lamp Kit	5	2-3	3	3
BAYUV102A	33" Retrofit UVC Lamp Kit	5	3½-5	4-5	4-5

- ① Must use filter frame when economizer/fresh air kit is used.
- ② Dry bulb control standard with economizer.
- ③ 2-Stage cooling control required when using economizer.
- ④ Do not use with electronic thermostats.
- ⑤ It is the responsibility of the installing dealer to properly size the ductwork for each specific application.
- ⑥ BAYCOVR112,118A will not cover BAYSQRD002A applications.
- ⑦ Does not contain barometric relief.
- ⑧ Max fresh air - 25%.
- ⑨ For non-continuous fan gas-heating applications, the damper opens only when the OD ambient is above 50° F.
- ⑩ It is the designer/engineer's responsibility to review product specifications prior to equipment selection to insure optimal performance and compliance to codes.
- ⑪ Temperature of mixed air entering the heat exchanger is monitored and fresh air intake may be reduced under certain conditions.
- ⑫ BAYACCDOR1A requires BAYFLTR101B & BAYACCDOR2A requires BAYFLTR201B. They are not backward compatible to BAYFLTR101/201A.

EXISTING CURB	NEW UNIT 4TC/WC/YC****A	USE BAYADAP0**A
BAYCURB030,38A	024-036	50
BAYCURB030,38A	042-060	52
BAYCURB033A	024-036	51
BAYCURB033A	042-060	53
BAYCURB034A	042-060	54

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

# Single Power Entry Kits Packaged Convertible 2-5 Tons

	SINGLE POWER ENTRY KIT	HEATER	4TCC4	4TCY4	4TCY5	4WCC4	4WCY4	4WCY5	4WCZ6
SINGLE PHASE (208/240v)	BAYSPEK060	BAYHTRV105	2-4	2-5	TBD	2-3	2-3		3
		BAYHTRV108	2-4	2-5		2	2		—
		BAYHTRV110	2-4	2-3		—	—		—
	BAYSPEK062	BAYHTRV105	5	—		3½-5	3½-5		4-5
		BAYHTRV108	5	—		2½-5	2½-5		3-5
		BAYHTRV110	5	3½-5		2-5	2-5		3-5
	BAYSPEK063	BAYHTRV115	2½-5	2½-5		2½-5	2½-5		3-5
		BAYHTRV120	4-5	3½-5		3½-5	3½-5		4-5
	SINGLE POWER ENTRY KIT	HEATER	4TCC3	4TCX3	4TCY4	4WCC3	4WCX3	4WCY4	4WCZ6
3 PHASE (208/240v)	BAYSPEK064	BAYHTRV315	—	—	—	3-5	3-5	3-5	3-5
		BAYHTRV320	4-5	4-5	4-5	4-5	4-5	4-5	4-5
	BAYSPEK065	BAYHTRV310	—	—	—	5	5	5	5
	BAYSPEK061	BAYHTRV305	3-5	3-5	3-5	3-5	3-5	3-5	3-5
		BAYHTRV308	3-5	3-5	3-5	3-5	3-5	3-5	3-5
		BAYHTRV310	3-5	3-5	3-5	3-4	3-4	3-4	3-4
		BAYHTRV315	3-5	3-5	3-5	—	—	—	—
3 PHASE (460v)	BAYSPEK061	BAYHTRV405	3-5	3-5	—	3-5	3-5	—	3-5
		BAYHTRV408	3-5	3-5	—	3-5	3-5	—	3-5
		BAYHTRV410	3-5	3-5	—	3-5	3-5	—	3-5
		BAYHTRV415	3-5	3-5	—	3-5	3-5	—	3-5
		BAYHTRV420	4-5	4-5	—	4-5	4-5	—	4-5

**For dimensional/outline drawings, please refer to Product Data.**

**For information on Roof Curbs, please refer to the Accessories/Information Tab.**

For complete equipment / combination selections, installation instructions and warranty information, please refer to Product Data/Ratings and/or Installers Guides and Limited Warranty Handbooks.



# Supplemental Heater Table Packaged Convertible 2-5 Tons

	BAYHTRV105 3.76/5.0 kW	BAYHTRV108 6.0/8.0 kW	BAYHTRV110 7.50/10.0 kW	BAYHTRV115 11.27/15.0 kW	BAYHTRV120 15.00/20.0 kW	BAYHTRV125 18.78/25.0 kW
4TCY5024A1	<b>TBD</b>					
4TCY5030A1						
4TCY5036A1						
4TCY5042A1						
4TCY5048A1						
4TCY5060A1						
4TCY4024A1	Y	Y	Y	--	--	--
4TCY4030A1	Y	Y	Y	Y	--	--
4TCY4036B1	Y	Y	Y	Y	--	--
4TCY4042B1	Y	Y	Y	Y	Y	Y
4TCY4048B1	Y	Y	Y	Y	Y	Y
4TCY4060A1	Y	Y	Y	Y	Y	Y
4TCC4024A1	Y	Y	Y	--	--	--
4TCC4030A1	Y	Y	Y	Y	--	--
4TCC4036A1	Y	Y	Y	Y	--	--
4TCC4042A1	Y	Y	Y	Y	--	--
4TCC4048A1	Y	Y	Y	Y	Y	--
4TCC4060A1	Y	Y	Y	Y	Y	Y
4WCZ6036B1	Y	Y	Y	Y	--	--
4WCZ6048B1	Y	Y	Y	Y	Y	Y
4WCZ6060B1	Y	Y	Y	Y	Y	Y
4WCY5024A1	Y	Y	Y	--	--	--
4WCY5030A1	Y	Y	Y	Y	--	--
4WCY5036A1	Y	Y	Y	Y	--	--
4WCY5042A1	Y	Y	Y	Y	Y	Y
4WCY5048A1	Y	Y	Y	Y	Y	Y
4WCY5060A1	Y	Y	Y	Y	Y	Y
4WCY4024A1	Y	Y	Y	--	--	--
4WCY4030A1	Y	Y	Y	Y	--	--
4WCY4036C1	Y	Y	Y	Y	--	--
4WCY4042B1	Y	Y	Y	Y	Y	Y
4WCY4048B1	Y	Y	Y	Y	Y	Y
4WCY4060B1	Y	Y	Y	Y	Y	Y
4WCC4024A1	Y	Y	Y	--	--	--
4WCC4030A1	Y	Y	Y	Y	--	--
4WCC4036A1	Y	Y	Y	Y	--	--
4WCC4042A1	Y	Y	Y	Y	--	--
4WCC4048A1	Y	Y	Y	Y	Y	--
4WCC4060A1	Y	Y	Y	Y	Y	Y

**For dimensional/outline drawings, please refer to Product Data.  
For information on Roof Curbs, please refer to the Accessories/Information Tab.**

For complete equipment / combination selections, installation instructions and warranty information, please refer to Product Data/Ratings and/or Installers Guides and Limited Warranty Handbooks.



# Supplemental Heater Table

## Packaged Convertible 2-5 Tons

	BAYHTRV305 3.76/5.0 kW (3PH)	BAYHTRV308 6.0/8.0 kW (3PH)	BAYHTRV310 7.50/10.0 kW (1PH)	BAYHTRV315 11.27/15.0 kW (3PH)	BAYHTRV320 15.0/20.0 kW (3PH)	BAYHTRV325 18.78/25.0 kW (3PH)
4TCY4036B3	Y	Y	Y	Y	--	--
4TCY4048B3	Y	Y	Y	Y	Y	Y
4TCY4060B3	Y	Y	Y	Y	Y	Y
4TCX3036A3	Y	Y	Y	Y	--	--
4TCX3048A3	Y	Y	Y	Y	Y	--
4TCX3060A3	Y	Y	Y	Y	Y	Y
4TCC3036A3	Y	Y	Y	Y	--	--
4TCC3048A3	Y	Y	Y	Y	Y	--
4TCC3060A3	Y	Y	Y	Y	Y	Y
4WCZ6036B3	Y	Y	Y	Y	--	--
4WCZ6048B3	Y	Y	Y	Y	Y	Y
4WCZ6060B3	Y	Y	Y	Y	Y	Y
4WCY4036A3	Y	Y	Y	Y	--	--
4WCY4048A3	Y	Y	Y	Y	Y	--
4WCY4060B3	Y	Y	Y	Y	Y	--
4WCX3036A3	Y	Y	Y	Y	--	--
4WCX3048A3	Y	Y	Y	Y	Y	--
4WCX3060A3	Y	Y	Y	Y	Y	Y
4WCC3036A3	Y	Y	Y	Y	--	--
4WCC3048A3	Y	Y	Y	Y	Y	--
4WCC3060A3	Y	Y	Y	Y	Y	Y
	BAYHTRV405 5.0 kW (3PH)	BAYHTRV408 8.0 kW (480V 3 PH)	BAYHTRV410 10.0 kW (3PH)	BAYHTRV415 15.0 kW (480V 3 PH)	BAYHTRV420 20.0 kW (480V 3 PH)	BAYHTRV425 25.0 kW (480V 3 PH)
4TCX3036A4	Y	Y	Y	Y	--	--
4TCX3048A4	Y	Y	Y	Y	Y	--
4TCX3060A4	Y	Y	Y	Y	Y	Y
4TCC3036A4	Y	Y	Y	Y	--	--
4TCC3048A4	Y	Y	Y	Y	Y	--
4TCC3060A4	Y	Y	Y	Y	Y	Y
4WCZ6036B4	Y	Y	Y	Y	--	--
4WCZ6048B4	Y	Y	Y	Y	Y	--
4WCZ6060B4	Y	Y	Y	Y	Y	--
4WCX3036A4	Y	Y	Y	Y	--	--
4WCX3048A4	Y	Y	Y	Y	Y	--
4WCX3060A4	Y	Y	Y	Y	Y	Y
4WCC3036A4	Y	Y	Y	Y	--	--
4WCC3048A4	Y	Y	Y	Y	Y	--
4WCC3060A4	Y	Y	Y	Y	Y	Y

**For dimensional/outline drawings, please refer to Product Data.**  
**For information on Roof Curbs, please refer to the Accessories/Information Tab.**

For complete equipment / combination selections, installation instructions and warranty information, please refer to Product Data/Ratings and/or Installers Guides and Limited Warranty Handbooks.