

MINI-SPLIT TRAY CABLE

600 VOLT

APPLICATIONS Suitable for use as follows:

- Tray Cable is a multi-conductor control, signal or power cable rated for 600 volts
- May be installed in raceways, conduit, cable trays, and outdoor locations where supported by a messenger wire
- Also suitable for direct burial
- Temperature rating at 75°C wet locations / 90°C dry locations

STANDARDS & REFERENCES

- UL listed as per UL 1277
- Conforms to applicable sections of UL 1581 and 1685
- RoHS Compliant
- Type TC

CONSTRUCTION

- Stranded copper conductors Type THHN or THWN
- The overall jacket is heat, moisture and sunlight resistant PVC



MINI-SPLIT WIRE 300 VOLT SHIELDED
/MINI-SPLIT TRAY CABLE 600 VOLT

600 Volt

Operating Temperature
+75°C Wet / +90°C Dry

PVC Jacket

WEIGHTS, MEASUREMENTS AND PACKAGING

SIZE (AWG) NUMBER OF CONDUCTORS	CONDUCTOR COLORS	JACKET THICKNESS NOM. (mils) / COLOR	APPROX. OD (mils)	APPROX. NET WT. / MFT
14/4	Black, Red, Blue, Orange	45 / Black	350	93
14/7	Black, Red, Blue, Orange, Yellow, Brown, Red with Black Stripe	45 / Black	413	145



greenSpec
RoHS Compliant

