

KwiKool® Cooling Systems

BioAir+ KBP600



Convertible - negative air, scrubber or both

Standard HEPA Filter

Dual UVC Lamps for Germicidal Irradiation

Internal cabinet walls covered with reflective insulation

Optional charcoal filter

3-Speed, Auto Restart

ETL Certified Performance



UPLA/HEPA Filter 99.99% @ > .3 Microns

UVC Light Wave Length UVC 17 Watts / Max 85 Watts

Fan Type Centrifugal **Direct Drive**

Air Flow H/M/L 600/475/350

Optional Discharge Flange 12"

Optional Ceiling Kit CK12-SS 12"



APPLICATION

Voltage @ 60Hz 115/1ph

Recommended Breaker Size (A)

Amps (A) **6.2**

15

Min/Max Voltage 105-125

Power Consumption (Amps) 6.2

Power Cord Gage/Length 14/6 Feet

Plug Configuration **NEMA 5-15**

SHIPPING/LOGISTICS/ HANDLING/QUALITY

	Shipping	Out of Carton
Weight (lbs.)	120	85
Height (in.)	43	38
Width (in.)	24	16.5
Depth (in.)	32	22.25
Weight With Optional Ceiling Kit (lbs.)	142	





spot-coolers.com 800-367-8675







ACCESSORIES









#	Description	#	Description	
1	Room Air Return	4	Cord Storage	
2	Control Panel (Touch Pad)	5	Filter Access Door	
3	Filtered Negative Air Supply	6	Cleaned Room Air Supply	



spot-coolers.com

800-367-8675