

Specification Sheet

Model # SA-37WR-GAE

Can be mounted inside the attic over an existing gable vent or roof penetration to supercharge the vents already there. Remains hidden and out of the weather, except for the roof mounted solar panel.

No large holes to cut in your roof.



Technical Information

Weight

Fan Weight: 5 lbs / 2.26 kg

Fan Packaged: 18 lbs. / 8.16 kg

Performance

Air Flow Rate: 900 to 1200 CFM Depending on solar exposure Ventilation: Up to 1600 sq.ft. Attic must support intake air for best performance

Electrical

Solar Panel: 37 watt, 17 to 22 DC, 1.5 amp, 36 mono-crystalline cell, solar cells with black back sheet

Motor: Solaro Max Aire Brushless DC Motor,10-22VDC

Material

Housing System: Spun Formed, Aircraft Grade Aluminum Fan Blade: 12" Aluminum, Factory Balanced Mesh Screen: Stainless Steel, 1/4" Mesh, Rodent Control Wiring: 18 Gauge Copper Conductors with PVC Insulation

ActiveAire

Housing & Flashing System

Aircraft grade, spun-formed aluminum for the utmost quality protection Inner housing system is

aerodynamically designed to produce the highest possible radial air exhaust Powder coated outer shell



AMERICAN MADE

Brushless Electronic Motor with Maximum Yield Technology. This new motor technology was developed by Solaro Energy - Our engineers leveraged lessons learned from our original brushless electronic motor that we used for over 12 years. This new motor technology offers about 30% better efficiency and air moving performance, with an amazing 100,000 hours average motor run time!

Solar Panel Brackets Extruded Aluminum

Mill finished Dimensions depth 0.60' 2"x2" Supports solar panel



Components

Solar Panel

37 watt, 1.5 amp proprietary, high purity, mono-crystalline cell solar panel Weather proof in the most severe conditions

High transparent, low iron tempered glass

Built for maximum performance and safety

Fan Blades

Specifically designed for the Solaro Aire solar powered ventilation system

12" - 5 blade aluminum fan, aerodynamically optimized blade to improve airflow Operates whisper quiet throughout the day




Interconnect Cable


Wire: 25' - 2 Conductor 18 Gauge stranded copper U.V. Rated Power transfer cable



Dimensions & Weight







Important Note: The Solaro Aire Attic Fan Ventilation System is 100% fire proof and all electrical components are hidden under the air diverting cowling creating an extremely safe and efficient ventilation system Limited Lifetime Warranty - See warranty details for additional information.

888-355-5786



solaroenergy.com